



Mirror cabinet	Dimension	Weight	Order number
built-in version, Standard-Version, cEGS/IAPM0®*, 2 mirror doors, 4 glass shelves, external switch, built-in only in combination with built-in set, LED (life span > 30,000 hours), LED module permanently enclosed, Mirrors cabinets require a GFCI 110 V 60 Hz power source and are hardwired to a circuit provided by the customer. , LED module 4000 kelvin light color 17 Watt	,		
Colors			
M00			
Variant			
	47 5/8" x 5 7/8" Ir	nch	LM782300000
Infobox			
# LM 7823 is available from stock, On/off function only possible with external wall switch, Built-in set please see page XXX, * Complies with following standards: UL 962 and CSA C22.2 No. 12-1982, Required specification for ordering:, - built-in yes / no			
Suitable products			
Magnetic strip in stainless steel , 3 1/2" Inch	3 1/2" Inch		UV9709
Recess frame for LM mirror cabinet Built-in frame: recess mounting frame in MDF White, width = X, height = 31 "; recess mounting frame in White Aluminum, width = X, height = 32 "; frame strength = 1 ", $49 5/8$ " x $5 1/2$ " Inch	49 5/8" x 5 1/2" Ir	nch	LM9878

All drawings contain the necessary measurements which are subject to standard tolerances. They are stated in inch & mm and are non-binding. Exact measurements, in particular for customized installation scenarios, can only be taken from the finished ceramic piece.