



Mirror cabinet	Dimension	Weight	Order number
Icon-Version, cEGS/IAPMO®*, LED dual light fields, 25 V LED ambient light (top & bottom 16-34 Watt), LED interlighting with auto on/off-function, 5 - 12 Watt, outer side mirror glass, 2 mirror doors, 2 glass shelves (clear glass panel inside mirror glass, integrated wave board for sm parts, progressive, synchronous adjustment of the light for direct and ambient light, touchless control panel (into on outer right side), dimming function and adjustment of light color with memory effect, LED (life span > 30,000 LED module permanently enclosed, mirror cabinets req GFCI 110 V 60 Hz power source, flat plug will be supplied the mirror cabinet	or ' e in s), back all color egrated f the hours), uire a		
Colors			
MB1 Champagne Matt MB2 Black Matt			
Variant			
LED module 2700 - 6500 kelvin light color, 65 Watt	40 1/8" x 6 1/8" Inc	h	XV7143
Infobox			
* Complies with following standards: UL 962 and CSA C	22.2 No. 12-1982, Required sp	ecification for order	ing:
Suitable products			
Magnetic strip in stainless steel , 3 1/2" Inch	3 1/2" Inch		UV9709
Box for mirror cabinet, 3 7/8" x 6 1/4" Inch	3 7/8" x 6 1/4" Inch		XV9948

All drawings contain the necessary measurements which are subject to standard tolerances. They are stated in inch & mm and are non-binding. Exact measurements, in particular for customized installation scenarios, can only be taken from the finished ceramic piece.