PRODUCT SPECIFICATIONS

Elkay WaterSentry Plus Commercial Water Dispenser Replacement Filter. Overall dimensions are 3-1/8" x 3-1/8" x 9-3/8".

Finish:	White (WH)
Dimensions:	3-1/8" x 3-1/8" x 9-3/8"
Shipping Weight:	2 lbs.
Flow Rate:	0.7 GPM (2.6 L/m)
Capacity:	3000 gal. (11356 L)
Temperature:	40-100°F (4-38°C)
Initial Pressure Drop:	2-5 PSI (14-34 kPa)
Maximum Pressure:	105 PSI (724 kPa)
Minimum Pressure:	20 PSI (138 kPa)
Water Inlet:	3/8" (9.5mm) O.D. tube
Water Outlet:	1/4" (6.4mm) O.D. tube

Special Note: Replacement Filter for ezH2O Liv Pro In-Wall Filtered Water Dispenser.

- Replacement filter for models with WaterSentry Plus LBWDC00 Water Dispenser.
- Filter should be replaced every 3000 gallons or 1 year after installation.
- Equipped with quick-disconnect, 1/4 turn installation, as well as automatic inlet shut-off valve that closes when filter is removed.
- Designed to reduce lead, particles and chlorine. Also reduces odors and discoloration from incoming water.
- Filter is certified to NSF 42 and 53 for lead, particulate class 1, chlorine, taste and odor reduction.

AMERICAN PRIDE. A LIFETIME TRADITION.
Like your family, the Elkay family has values and traditions that endure. For almost a century, Elkay has been a family-owned and operated company, providing thousands of jobs that support our families and communities.

Product Compliance: Buy American Act
NSF 372 (lead free)
NSF 42
NSF 53

Drains are listed by IAPMO® as meeting the applicable requirements of the Uniform Plumbing Code®, International Plumbing Code®, and National Plumbing Code of Canada.

NO IMAGE AVAILABLE

PART:_____QTY: _____

PROJECT:_____

CONTACT:_____

DATE:_____

NOTES:_____

APPROVAL:_____

Elkay REV 06052021
ECF3000

1333 Butterfield Road, Suite 200
Downers Grove, IL 60515

© 2021   Page 1
ECF3000_spec.pdf