



### PRODUCT DESCRIPTION

Within an atmosphere of peaceful bliss and ethereal light, you'll find Serenity™. Loved for its perpetually elegant design and beautiful ambient wall glow, this splendid centerpiece can transform any room into a calming oasis.

### SPECIFICATION STATEMENT

Solution shall consist of a mirror with wall-glow accent light around the mirror which provides uniform light to the walls at all edges of the mirror. It shall have corrosion-resistant glass. The mirror shall use dimmable, replaceable LEDs with greater than or equal to 90 CRI (color rendering index). Product will be made in USA and have a 7-year limited warranty.

### THE ELECTRIC MIRROR ADVANTAGE

- ☑ Global mirror technology leader for over 20 years
- ☑ More installations than all competitors combined
- ☑ Realistic warranty you can believe in and trust
- ☑ Lowest total cost of ownership
- ☑ U.S. based customer service support
- ☑ 125,000 square foot American manufacturing facility

### FEATURES AND BENEFITS

- Copper-free, corrosion-resistant DuraMirror™ glass
- Wall-glow ambient lighting with diffuser for a finished side view
- Environmentally sustainable
- Energy efficient
- Fast lead times
- Easy installation
- ADA Compliant
- Title 24 compliance available
- 7-year limited warranty
- Covered by one or more patents
- Proudly made in the USA

### AVAILABLE OPTIONS

- Keen™ SmartDim™ Technology<sup>1</sup>
- Vive™ SmartSound™ Technology<sup>1,2</sup>
- Seamless™ SmartTime™ Technology<sup>1,2</sup>
- Night Light<sup>1,2</sup>
- Defogger<sup>1</sup>
- Forward-phase dimming
- Diamond Clear™ DuraMirror™ glass<sup>2</sup>
- 2,700K CCT<sup>2</sup>
- Custom mirror sizes<sup>2</sup>

### LIGHTING SPECIFICATIONS

- Natural-looking LED light color
- Replaceable LEDs
- CRI: 90+
- CCT: 3,000 Kelvin
- 695 lumens per foot
- Calculated L<sub>70</sub> 52,000-hour LED lifespan
- Maximum 100 lumens per watt efficacy

### SAFETY SPECIFICATIONS

- Entire assembly meets UL/cUL standards
- International certifications
- Safety-backed mirror

<sup>1</sup> See technology specification sheets for more information.

<sup>2</sup> Minimum order quantity required.

**INSTALLATION SPECIFICATIONS**

- 120V-240V hardwire electrical connection; provide 36" whip; junction box not required
- Chassis should be mounted to wall studs; mounting holes are provided
- Fixture should be controlled by an on/off switch
- Installation wiring may be different on mirrors equipped with additional options

**MODELS**

| Base Model*                 | Dimensions                                       | Power Requirements |
|-----------------------------|--|--------------------|
| SER2-24.00x36.00-L7CSHD-30K | 24"W x 36"H x 1.75"D<br>(610mm x 914mm x 44mm)   | 120/240 VAC, 67W   |
| SER2-30.00x42.00-L7CSHD-30K | 30"W x 42"H x 1.75"D<br>(762mm x 1067mm x 44mm)  | 120/240 VAC, 85W   |
| SER2-36.00x36.00-L7CSHD-30K | 36"W x 36"H x 1.75"D<br>(914mm x 914mm x 44mm)   | 120/240 VAC, 85W   |
| SER2-42.00x42.00-L7CSHD-30K | 42"W x 42"H x 1.75"D<br>(1067mm x 1067mm x 44mm) | 120/240 VAC, 100W  |
| SER2-48.00x36.00-L7CSHD-30K | 48"W x 36"H x 1.75"D<br>(1219mm x 914mm x 44mm)  | 120/240 VAC, 100W  |
| SER2-54.00x42.00-L7CSHD-30K | 54"W x 42"H x 1.75"D<br>(1372mm x 1067mm x 44mm) | 120/240 VAC, 120W  |
| SER2-60.00x36.00-L7CSHD-30K | 60"W x 36"H x 1.75"D<br>(1524mm x 914mm x 44mm)  | 120/240 VAC, 120W  |
| SER2-66.00x42.00-L7CSHD-30K | 66"W x 42"H x 1.75"D<br>(1676mm x 1067mm x 44mm) | 120/240 VAC, 140W  |

\*Base model number shown only. To specify additional options, contact Electric Mirror at sales@electricmirror.com.

**DIMENSIONAL DRAWING** (Not to scale.)

