

MAGNETIC TRANSFORMER

OUTDOOR 150W/300W



High quality stainless steel construction for quality protection against the elements.

Features:

- Isolated output power per NEC and UL safety requirements
- Auto-reset; Short-circuit, Overload and Thermal protection
- Soft Start, Dimmable, and Outdoor grade material
- Timer and Photocell option inside housing

SPECIFICATIONS

INPUT VOLTAGE	120V AC 50/60Hz
INPUT CURRENT	150W: 120V, 1.25A 300W: 120V, 2.5A
OUTPUT VOLTAGE	120V: 12V AC
OUTPUT CURRENT	150W: 12.5A 300W: 25.0A
MOUNTING OPTIONS	Wall (12" above finished grade)
DIMMING	Magnetic Low Voltage
EFFICIENCY	80%
POWER FACTOR	>98%
CAST TC*	90°C max
PROTECTION	Input/Output
STORAGE	-30°C/+90°C
HUMIDITY	95% RH max
WET LISTED	IP 60, 67
WARRANTY*	5 Years

*Visit techlighting.com for specific warranty limitations and details.

As a general rule when using LED fixtures, we do not recommend using greater than 70% of specified maximum wattage on the transformer due to inrush current. For assistance, please contact our technical support department.



MAGNETIC TRANSFORMER
shown in stainless steel



MAGNETIC TRANSFORMER
shown in stainless steel


ORDERING INFORMATION

PRODUCT	HOUSING	DIMMING
7000T150T OUTDOOR, MAGNETIC, 150W, 120V	STAINLESS STEEL	MAGNETIC
7000T300T OUTDOOR, MAGNETIC, 150W, 120V	STAINLESS STEEL	MAGNETIC

*OUTDOOR RATED, ORDERED SEPARATELY.

MAGNETIC TRANSFORMER

OUTDOOR 150W/300W



Magnetic Transformer

PROJECT INFO

FIXTURE TYPE & QUANTITY	JOB NAME & INFO	NOTES



VISUAL COMFORT & Co.

7400 Linder Avenue, Skokie, Illinois 60077

T 847.410.4400



© 2022 Tech Lighting, L.L.C. All rights reserved. The "Tech Lighting" graphic is a registered trademark. Tech Lighting reserves the right to change specifications for product improvements without notification.