





Company. Basic shower will conform to ANSI-Z-124.2. Unit to include stainless steel curtain rod; Symmons® pressure balance mixing valve with concealed check stops; Moen® hand-held shower head with hose and chrome-plated slide bar; stainless steel wrap-around grab bar; stainless steel recessed soap dish.

Furnish and install one-piece gel-coated fiberglass shower stall Model 39-62H designed for barrier-free use as manufactured by Florestone Products

Supplied with 2" brass drain.

Shower curtain optional.

Florestone

Model 39-62H

0.D. = 62" x 39" x 77"

I.D. = 60" x 37" x 76" Weight: 285 lbs.

Architect's **Specifications**

Barrier-Free Shower

Curtain Size: 72" x 72".

Standard Color: White.

Special order colors available.

Standards:

I.A.P.M.O. File No. 0687 ANSI-Z-124.2



FLOREST A Spec Above.

FLORESTONE PRODUCTS CO., INC.

28	51 Falcon Drive	•	Ma	dera,	CAS	93637
T.	559.661.4171	•	T.	800	446	8827
F.	559.661.2070	•	f	lores	tone	.com

Dimensions subject to change without notice.

Contact Florestone Products to verify product specifications.

Dimensions may vary $\pm 1/4$ " inch. Please check unit before installation.

For barrier-free installation, contractor shall provide 5/8" minimum recess for curb in sub floor.

ADA compliance when accessories installed by manufacturer. Note: Exter[®] is a Registered Trade Mark of Symmons Industries, Inc. Mone[®] is a Registered Trade Mark of Symmons Industries, Inc.