

Specifications

- Metal construction for durability and reliability
- Pressure balancing volume control with 2 way diverter with shut off or sharing
- Max-temperature limit stop for added safety
- Integral stop check valves for easy maintenance
- 5-function shower head and 8" shower arm
- Jovian tub spout with fluid speed connection
- Requires pressure balancing valve with shut off F1012B or F1012B-PEX or F1012B-PEX-W OR
- Requires pressure balancing valve with sharing F1012B-SHARE or F1012B-SHARE-PEX or F1012B-SHARE-PEX-W
- Valve and trim packages are sold separately

Finish

- CP (Chrome)
- BN (PVD Brushed Nickel)

Flow Rate

- Shower head 1.8 gpm @ 60 psig
- Tub spout 4.5 gpm @ 60 psig

Codes and Standards

- ANSI/ASME A112.18.1
- CSA B125.1
- IAPMO / cUPC

Warranty

- Limited Lifetime Faucet Warranty against material and manufacturing defects for residential use.
- 2 Year Limited Warranty on all industrial, commercial and business applications.

**fluid Jovian Series
Shower Head and Tub Spout
Trim Kit
Model: F212305T**

Includes:

F1001T

FP801013

FP6021041

FP605752

FP6001143-2PB

FP20100

FP6027008

FP6016034

Sleeve Tube and Cap

Diverter Sleeve Tube

Jovian Handle

Square Diverter Handle

Square Cover Plate

5-Function Shower Head

8" Shower Arm

Jovian Tub Spout

