Gas Range, 48", 6 Burners with Grill, LPG

Series 7 | Professional

Stainless Steel | LPG




A striking addition to your kitchen, with six powerful gas burners and two gas ovens giving you a combined capacity of 7.7 cu ft.

- Top burner heat of 19,000 BTU, for seriously fast boiling
- Expansive 7.7 cu ft total oven capacity across two oven cavities
- Non-tip full-extension shelves in main cavity for safe removal of hot dishes

DIMENSIONS

Height	35 ³ / ₄ - 36 ³ / ₄ '
Width	47 ⁷ /8 ′
Depth	29 ¹ / ₈ ′



FEATURES & BENEFITS

Cooktop power

Sealed Dual Flow Burners™ deliver cooktop power up to 23,500 BTU (NG models) for seriously fast boiling right down to a precise 140°F full surface simmer with the gentlest of flames.

Total control

Precise control across high and low settings is delivered through the halo-illuminated cooktop dials. The ovens have true convection and electronic oven control for precise and consistent temperatures.

Easy to clean

A sealed cooktop surface coupled with a commercial-style stainless steel finish means your cooktop simply needs a quick wipe to keep it looking good as new.

Instant visibility

Control dials have halo-illumination glowing white - heating up; orange - temperature reached; red - self-cleaning mode. The oven is illuminated by two powerful incandescent lights.

Cooking flexibility

The cooktop is designed for easy access to any burner with grates you can smoothly slide pots across. The oven is large enough to hold full size baking sheets.

<<Missing Feature Title>>

This range has been carefully crafted in every detail from performance to durability using quality materials.

SPECIFICATIONS

Accessories

Square handle option AH-R48

Controls

Metal illuminated dials

Gas requirements

Fitting and pipe ½ NPT, min. %" Ø flex line

Main oven features

Broil pan

Capacity total (AHAM)

5.3 cu ft

Capacity usable (AHAM) 3.9 cu ft

Electronic oven control •

Full extension telescopic racks	3
Infrared Broiler	•
Internal Light	•
Shelf positions	5
Main oven functions	
Bake	•
Broil	•
Convection bake	•
Number of main oven	3
Oven performance	
Main oven - Bake power	22,000 BTU
Main oven - Broil power	19,000 BTU
Secondary oven - Bake power	18,000 BTU
Power requirements	
Amperage	15A
Supply frequency	60Hz
Supply voltage	120V
Product dimensions	
Depth	29 ¹ / ₈ "
Height	35 ³ / ₄ - 36 ³ / ₄ "
Width	47 ⁷ / ₈ "
Rangetop features	
Sealed Dual Flow Burners™	6
Sealed Dual Flow Burners™ Sealed range top	6

19,000 BTU 13,000 BTU 13,000 BTU 13,000 BTU 15,000 BTU 15,000 BTU 10,000 BTU 98,000 BTU
13,000 BTU 13,000 BTU 13,000 BTU 15,000 BTU 15,000 BTU 15,000 BTU
13,000 BTU 13,000 BTU 15,000 BTU 19,000 BTU 15,000 BTU 10,000 BTU
13,000 BTU 15,000 BTU 19,000 BTU 15,000 BTU 10,000 BTU
15,000 BTU 19,000 BTU 15,000 BTU 10,000 BTU
19,000 BTU 15,000 BTU 10,000 BTU
15,000 BTU 10,000 BTU
10,000 BTU
98,000 BTU
•
2.4 cu ft
1.7 cu ft
•
•
5
•
2

ı	Parts and labor	Limited 2 years
_		
S	KU	71349

TEST The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. ? Fisher & Paykel Appliances Ltd 2020

Other product downloads available at fisherpaykel.com



User Guide



Service & Warranty Booklet



Installation Guide



Resources (zip)



A PEACE OF MIND SALE

24 Hours 7 Days a Week Customer Support

T 1.888.936.7872 **W**www.fisherpaykel.com