QUICK REFERENCE GUIDE > RHV3-484-L

Dual Fuel Range, 48", 4 Burners, 4 Induction Zones, Self-cleaning, LPG

Series 9 | Professional

Stainless Steel | LPG




With both induction and gas cooktops and two convection ovens, you're ready to create a feast – guided by an intuitive touchscreen.

- Guided cooking using your touchscreen makes it simple to cook by food, function or recipe.
- Top burner heat of 19,000 BTU, for seriously fast boiling
- Four induction cooking zones, which can be paired to form two SmartZones

6.9 cu ft total oven capacity across two oven cavities

DIMENSIONS

Height	35 ³ / ₄ - 36 ³ / ₄ "
Width	47 ⁷ / ₈ "
Depth	29 ¹ / ₈ "



FEATURES & BENEFITS

Cook with confidence

Our touchscreen interface provides an intuitive guided cooking experience that helps deliver perfect results, whether you've been cooking all your life or just starting out. Cook with a favorite method, a hero ingredient, or a go-to cooking function or recipe. The screen tilts for improved ergonomics and optimal visibility while cooking.

Generous capacity

Two independently operating cavities provide a large total capacity of 4.8 cu. ft. in the main cavity and 2.1 cu. ft. in the secondary. That's enough room for a 32 lb turkey in one oven, and your sides in the other.

Cooking flexibility

No matter what you're cooking, you've got the right heat to get perfect results. Each of the 15 oven functions in the main cavity and 11 in the secondary have been extensively researched and carefully designed to cater to a broad range of dishes and cooking styles. The handy food probe helps you monitor your progress.

Cooktop power

On the gas side of the cooktop, Sealed dual flow burners deliver power up to 19,000 BTU, while the induction side delivers up to 3700W. This finely tuned cooktop provides instant and immediate control from the highest heat to the most gentle simmer.

Design quality

This range has craftsmanship in every detail, with real stainless steel, cast-iron trivets, and beautifully weighted, halo illuminated dials. Each cavity features incandescent lights and full extension telescopic racks. From the robust legs to the powerful cooktop, this Range is built to last.

Easy to clean

The oven features a self-cleaning function and self-clean proof side racks, which don't need to be removed when using this function. The induction zones only need a quick wipe after use to keep them clean.

SPECIFICATIONS

Accessories

Square handle option

AH-R48

QUICK REFERENCE GUIDE > RHV3-484-L

Cleaning		Electronic oven control	•		010014/770014
Pyrolytic self-clean	•	Full extension telescopic	2	Left rear zone rating	2100W/3700W
		Internal light	•	Max burner power	19000BTU
Controls		True convection	•	Power back left	13000BTU
High resolution display	•			Power back right	13000BTU
Metal illuminated dials	•	Oven nerfermance		Power front left	19000BTU
Sabbath mode	•	Oven performance		Power front right	13000BTU
Wifi connectivity	•	Main oven - True convection	2500W	Right front zone rating	2100W/3700W
will confidentially				Right rear zone rating	2100W/3700W
		Power requirements		Total cooktop power	58000BTU
Gas requirements		Supply frequency	60Hz		
Fitting and pipe	½ NPT, min. %" Ø flex line	Supply voltage	120 - 240V	Safety	
Supply Pressure (LPG)	11" to 14" W.C			Pan detection system	•
		Product dimensions		Safety time out	•
Main oven features		Depth	29 ¹ / ₈ "	Surface hot indicators	•
Capacity total (AHAM)	4.8cu ft	Height	35 ³ / ₄ - 36 ³ / ₄ "		
Capacity usable (AHAM)	3.8cu ft	Width	47 ⁷ / ₈ "	Secondary oven features	
Large broil pan	•			Capacity total (AHAM)	2.1cu ft
Self cleaning	•	Rangetop features		Capacity usable (AHAM)	1.8cu ft
Shelf positions	5	Gentle heat	3 settings (111°F, 158°F, 201°F)	Shelf positions	5
True convection	•	Heat settings	9	Sileii positions	,
		Induction cooking technology	•	Secondary oven functions	
Main oven functions		PowerBoost	•	Bake	2450W
Bake	4600W	Sealed Dual Flow Burners™	4	Broil	3600W
Broil	4000W	Simmer on all burners	140°F	Convection bake	
Clean	•	SmartZone	2	Convection broil	•
Convection broil	•	Vent trim included	Flat vent trim	Number of secondary oven	11
Number of main oven	15	Zone bridging	•	——————————————————————————————————————	
Oven features		Pangoton Porformance		Warranty	
Concealed element	•	Rangetop Performance	210014/770014	Parts and labor	Limited 2 Years Parts & Labor
22664.64 6.6.116116		Left front zone rating	2100W/3700W		

QUICK REFERENCE GUIDE > RHV3-484-L Date: 24.12.2020 > 3

SKU 81891

TEST The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. ? Fisher & Paykel Appliances Ltd 2020

Other product downloads available at fisherpaykel.com



User Guide



Service & Warranty Booklet



Installation Guide



Resources (zip)



A PEACE OF MIND SALE

24 Hours 7 Days a Week Customer Support

T 1.888.936.7872 **W**www.fisherpaykel.com