QUICK REFERENCE GUIDE > RGV3-366-L Date: 11.02.2021 > 1

Gas Range, 36", 6 Burners, LPG

Series 7 | Professional

Stainless Steel | LPG



Professional style with power. 17,000 BTU gas burners paired with a large capacity gas oven.

- Top burner heat of 17,000 BTU, for seriously fast boiling
- Convection oven with 5.3 cu ft total capacity
- Non-tip full-extension shelves in main cavitiy for safe removal of hot dishes
- Made from quality materials and real stainless steel

DIMENSIONS

Height	35 ³ / ₄ - 36 ³ / ₄ "
Width	35 ⁷ / ₈ "
Depth	29 1/8 "

FEATURES & BENEFITS

Generous capacity

Featuring a generous total capacity of 5.3 cu ft, with enough room to fit a 32 lb turkey and full-sized baking sheets.

Cooktop power

Sealed Dual Flow Burners™ deliver cooktop power up to 17,000 BTU for seriously fast boiling right down to a precise 140°F full surface simmer with the gentlest of flames.

Cooking flexibility

<>

Design quality

This range has craftsmanship in every detail, with real stainless steel, cast-iron trivets, and titanium coated dials. Each cavity features incandescent lights and full extension telescopic racks. From the robust legs to the powerful legs to the powerful cooktop, the Range is built to last.

Easy to clean

Cleaning up spills is effortless with the continuous, porcelain basepan. Your cooktop simply needs a quick wipe to keep it looking good as new.

Total control

Precise control across high and low settings is delivered through the halo-illuminated cooktop dials.

SPECIFICATIONS

Accessories

Square handle option	AH-R36
Capacity	
Shelf positions	5
Total capacity	5.3 cu ft
Usable capacity	4.0 cu ft
Controls	
Metal illuminated dials	•
Star K Certification	•
Titanium coated, illuminated	•
Gas requirements	
Fitting and pipe	½ NPT, min. %" 🛭 flex line
Supply Pressure (LPG)	11" to 14" W.C
Oven features	
Broil pan	•
Electronic oven control	•
Full extension telescopic	2
Infrared Broiler	•
Internal light	•
Oven functions	
Bake	
Broil	
Convection bake	•
Number of functions	4
Slow cook	•

QUICK REFERENCE GUIDE > RGV3-366-L Date: 11.02.2021 > 2

Oven performance	
Bake power	21,500 BTU
Broil power	19,000 BTU
Power requirements	
Amperage	15A
Supply frequency	60Hz
Supply voltage	120V
Product dimensions	
Depth	29 ¹ / ₈ "
Height	35 ³ / ₄ - 36 ³ / ₄ "
Width	35 ⁷ / ₈ "
Rangetop features	
Sealed Dual Flow Burners™	6
Sealed range top	•
Simmer on all burners	140°F
Vent trim included	Flat vent trim
Rangetop Performance	
Max burner power	17,000 BTU
Power back centre	13,000 BTU
Power back left	13,000 BTU
Power back right	13,000 BTU
Power front centre	15,000 BTU
Power front left	17,000 BTU
Power front right	17,000 BTU

Recommended back guards and ventilation		
Combustible situation	BGRV3-3036H	
Non combustible situation	BGRV2-3036 / BGRV2-1236	
Recommended hood	HCB36-6_N (36"" Professional	
Safety		
ADA compliant	•	
Full extension telescopic	•	
Warranty		
Parts and labor	2 years	
SKU	82003	

TEST The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. ? Fisher & Paykel Appliances Ltd 2020

Other product downloads available at fisherpaykel.com



User Guide



Service & Warranty Booklet



Installation Guide



A PEACE OF MIND SALE

24 Hours 7 Days a Week Customer Support

T 1.888.936.7872 Wwww.fisherpaykel.com