

Gas Range, 30", 5 Burners, LPG

Series 7 | Professional

Stainless Steel | LPG



Professional style and performance, with high power burners delivering high heat or the most gentle simmer.

- Top burner heat of 17,000 BTU, for seriously fast boiling
- Convection oven with 4.6 cu ft total capacity
- Non-tip full-extension shelves in main cavity for safe removal of hot dishes
- Made from quality materials and real stainless steel

DIMENSIONS

Height	35 ³ / ₄ - 36 ³ / ₄ "
Width	29 ⁷ / ₈ "
Depth	29 ¹ / ₈ "

FEATURES & BENEFITS

Cooktop power

Sealed Dual Flow Burners™ deliver cooktop power up to 17,000 BTU for seriously fast boiling right down to a precise 140°F full surface simmer with the gentlest of flames.

Cooking flexibility

<>

Design quality

This range has craftsmanship in every detail, with real stainless steel, cast-iron trivets, and titanium coated dials. Each cavity features incandescent lights and full extension telescopic racks. From the robust legs to the powerful cooktop, the Range is built to last.

Easy to clean

<>

Total control

Precise control across high and low settings is delivered through the halo-illuminated cooktop dials.

SPECIFICATIONS

Accessories

Square handle option	AH-R30
----------------------	--------

Capacity

Shelf positions	5
-----------------	---

Total capacity	4.6 cu ft
Usable capacity	3.4 cu ft

Cleaning

- Easy clean porcelain basepan

Controls

- Metal illuminated dials
- Star K Certification
- Titanium coated, illuminated

Gas requirements

Fitting and pipe	½ NPT, min. ⅝" flex line
Supply Pressure (LPG)	11" to 14" W.C

Oven features

- Broil pan
- Electronic oven control
- Full extension telescopic 2
- Infrared Broiler
- Internal light

Oven functions

- Bake
- Broil
- Convection bake
- Number of functions 4
- Slow cook

Oven performance

Bake power	21,500 BTU
Broil power	19,000 BTU

Non combustible situation	BGRV2-3030 / BGRV2-1230
Recommended hood	HCB30-6_N (Professional

Other product downloads available at fisherpaykel.com

- [↓](#) User Guide
- [↓](#) Service & Warranty Booklet
- [↓](#) Installation Guide

Power requirements

Amperage	15A
Supply frequency	60Hz
Supply voltage	120V

Safety

- ADA compliant •
- Full extension telescopic •

Product dimensions

Depth	29 ¹ / ₈ "
Height	35 ³ / ₄ - 36 ³ / ₄ "
Width	29 ⁷ / ₈ "

Warranty

Parts and labor	2 years
-----------------	---------

SKU	82007
-----	-------

TEST The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. ? Fisher & Paykel Appliances Ltd 2020

Rangetop features

Sealed Dual Flow Burners™	5
Sealed range top	•
Simmer on all burners	140°F
Vent trim included	Flat vent trim

Rangetop Performance

Max burner power	17,000 BTU
Power back left	11,500 BTU
Power back right	11,500 BTU
Power centre	17,000 BTU
Power front left	15,000 BTU
Power front right	15,000 BTU
Total cooktop power	70,000 BTU

Recommended back guards and ventilation

Combustible situation	BGRV3-3030H
-----------------------	-------------

**A PEACE OF MIND SALE****24 Hours 7 Days a Week Customer Support****T 1.888.936.7872 Wwww.fisherpaykel.com**