QUICK REFERENCE GUIDE > VB30SDEB1

# Vacuum Seal Drawer, 30"

Series 9 | Minimal

Black



Prepares food for sous vides cooking, with vacuum sealing for marinating, food storage and portioning and resealing.

- Effortless preparation for sous vide cooking
- Three levels of vacuum and heat sealing for food storage, marinating or portioning
- Part of our suite of companion products, designed to match aesthetically for flexible configurations
- Intuitive touch controls for ease of use

#### **DIMENSIONS**

Height	10 11/16 "
Width	29 15/16 "
Depth	22 1/2 "

## **FEATURES & BENEFITS**

#### Complementary design

Designed to match the Fisher & Paykel family of appliances, the Vacuum Seal Drawer is the ideal companion product for our Minimal style ovens.

#### Three levels of vacuum and heat sealing

Vacuum seal food to intensify flavors, infuse marinades and retain freshness. Effortlessly prepare food for sous vide cooking in optimal conditions.

### **SPECIFICATIONS**

#### Accessories

ernal vacuuming accessory	Adapter, stopper and tube
ge size BPA-free vacuum	50 bags, Part 793034
all size BPA-free vacuum	50 bags, Part 793033

#### Capacity

Maximum vacuum seal bag	9
Storage drawer	•
Usable capacity	0.3cu ft
Usable height	3 <sup>3</sup> / <sub>8</sub>

#### Cleaning

Easy clean glass lid	•
Fasy clean stainless steel	

Pump pressure Vacuum levels Vacuum sealing levels  Power requirements  Amperage Maximum power Power cord length Power outlet Supply frequency Supply voltage  Product dimensions Adjustable front door panel to Depth  10 b  10 b  11 c  12 1/2	Removable sealing bar and	
Intuitive capacitive touch Maintenance and moisture Push-to-open drawer Standby mode  Performance External vacuuming Prepare food for sous-vide Pump power 1500 Pump pressure 10 b Vacuum levels Vacuum sealing levels  Power requirements Amperage 100 Maximum power 3200 Power cord length 7 Power outlet 3-prong grounding-type Supply frequency 600 Supply voltage 1100  Product dimensions Adjustable front door panel to Depth 22 1/2	Controls	
Maintenance and moisture Push-to-open drawer Standby mode  Performance External vacuuming Prepare food for sous-vide Pump power 1500 Pump pressure 10 b Vacuum levels Vacuum sealing levels  Power requirements Amperage 100 Maximum power 3200 Power cord length 70 Power outlet 3-prong grounding-type Supply frequency 600 Supply voltage 1100  Product dimensions Adjustable front door panel to Depth 22 1/2	Audio feedback	•
Push-to-open drawer Standby mode  Performance External vacuuming Prepare food for sous-vide Pump power 1500 Pump pressure 10 b Vacuum levels Vacuum sealing levels  Power requirements Amperage 100 Maximum power 3200 Power cord length 70 Power outlet 3-prong grounding-type Supply frequency 600 Supply voltage 1100  Product dimensions Adjustable front door panel to Depth 22 1/2	Intuitive capacitive touch	•
Performance  External vacuuming Prepare food for sous-vide Pump power Pump pressure Vacuum levels Vacuum sealing levels  Power requirements Amperage Maximum power Power cord length Power outlet Supply frequency Supply voltage  Product dimensions Adjustable front door panel to Depth  External vacuuming Prepare food for sous-vide Pump power 150' Pump pressure 10 b 10 b 10 b 10 c	Maintenance and moisture	
Performance External vacuuming Prepare food for sous-vide Pump power 1500 Pump pressure 10 b Vacuum levels Vacuum sealing levels  Power requirements Amperage 100 Maximum power 3200 Power cord length 70 Power outlet 3-prong grounding-type Supply frequency 600 Supply voltage 110  Product dimensions Adjustable front door panel to Depth 22 1/2	Push-to-open drawer	•
External vacuuming Prepare food for sous-vide Pump power 1500 Pump pressure 10 b Vacuum levels Vacuum sealing levels  Power requirements Amperage 100 Maximum power 3200 Power cord length 7 Power outlet 3-prong grounding-type Supply frequency 600 Supply voltage 110  Product dimensions Adjustable front door panel to Depth 22 1/2	Standby mode	•
Prepare food for sous-vide  Pump power 150  Pump pressure 10 b  Vacuum levels  Vacuum sealing levels  Power requirements  Amperage 10  Maximum power 320  Power cord length 7  Power outlet 3-prong grounding-tyst  Supply frequency 60  Supply voltage 110  Product dimensions  Adjustable front door panel to  Depth 22 1/2	Performance	
Pump power 1500 Pump pressure 10 b Vacuum levels Vacuum sealing levels  Power requirements Amperage 10 Maximum power 3200 Power cord length 7 Power outlet 3-prong grounding-type Supply frequency 600 Supply voltage 110  Product dimensions Adjustable front door panel to Depth 22 1/2	External vacuuming	•
Pump pressure Vacuum levels Vacuum sealing levels  Power requirements Amperage Maximum power Power cord length Power outlet Supply frequency Supply voltage  Product dimensions Adjustable front door panel to Depth  10 b	Prepare food for sous-vide	•
Vacuum levels  Vacuum sealing levels  Power requirements  Amperage 10  Maximum power 320  Power cord length 7  Power outlet 3-prong grounding-type  Supply frequency 60  Supply voltage 110  Product dimensions  Adjustable front door panel to  Depth 22 1/2	Pump power	150W
Power requirements  Amperage 10  Maximum power 3200  Power cord length 7  Power outlet 3-prong grounding-tyst Supply frequency 600  Supply voltage 110  Product dimensions  Adjustable front door panel to Depth 22 1/2	Pump pressure	10 bar
Power requirements  Amperage 10  Maximum power 320  Power cord length 7  Power outlet 3-prong grounding-type Supply frequency 600  Supply voltage 110  Product dimensions  Adjustable front door panel to Depth 22 1/2	Vacuum levels	3
Amperage 10  Maximum power 320  Power cord length 7  Power outlet 3-prong grounding-type Supply frequency 60P  Supply voltage 110  Product dimensions  Adjustable front door panel to Depth 22 1/2	Vacuum sealing levels	3
Maximum power  Power cord length  Power outlet  Supply frequency  Supply voltage  Product dimensions  Adjustable front door panel to  Depth  320'  3-prong grounding-typ  60'  3-prong grounding-typ  60'  22'/2	Power requirements	
Power cord length  Power outlet  Supply frequency  Supply voltage  Product dimensions  Adjustable front door panel to  Depth  Depth	Amperage	10A
Power outlet  Supply frequency  Supply voltage  Product dimensions  Adjustable front door panel to  Depth  3-prong grounding-type  60H  22 1/2	Maximum power	320W
Supply frequency Supply voltage  110  Product dimensions Adjustable front door panel to Depth  22 1/2	Power cord length	70
Product dimensions  Adjustable front door panel to  Depth  22 1/2	Power outlet	3-prong grounding-type
Product dimensions  Adjustable front door panel to  Depth 22 1/2	Supply frequency	60Hz
Adjustable front door panel to  Depth  22 1/2	Supply voltage	110V
Depth 22 1/2	Product dimensions	
	Adjustable front door panel to	•
Height 10 <sup>11</sup> / <sub>16</sub>	Depth	22 1/2 "
	Height	10 11/16 "

Width

QUICK REFERENCE GUIDE > VB30SDEB1 Date: 10.12.2020 > 2

Safety	
BPA-free vacuum seal bags	100 bags included
Full extension telescopic	•
Warranty	
Parts and labor	2 years
SKU	82121

TEST The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. ? Fisher & Paykel Appliances Ltd 2020

# Other product downloads available at fisherpaykel.com



Service & Warranty Booklet

