


Home Comfort FFHP242ZQ2

Multi-Zone Outdoor Condenser



FFHP242ZQ2 Outdoor

Product Dimensions Condenser (Outdoor) Model

Height	31-1/8"
Width	38-5/8"
Depth	16-13/16"

More Easy-To-Use Features

Multi-Speed Fan

Features three different fan speeds, for more cooling flexibility.

Effortless™ Restart

Automatically resumes operating at its previous settings when power is restored to your unit.

Effortless™ Clean Filter

Our antibacterial filter reduces bacteria, room odors and other airborne particles for a healthier, more comfortable environment.

Ready-Select® Controls

Easily select options with the touch of a button.

Electronic Controls

Allow you to set the comfort level to your preference, while a convenient temperature readout displays the set temperature.

Performance	BTUs
Cool	28,000
Heat	28,400

Signature Features

Quick Cool & Quick Warm

When you need to cool down quickly or warm up faster, use the quick cool/warm mode to speed up the fan.

Programmable 24-Hour On/Off Timer

Customize times to fit your schedule for immediate comfort when you get home. The built-in timer allows you to preset the unit to turn on and off in half-hour increments.

Effortless™ Temperature Control


Our air conditioners maintain the preset room temperature, so you will remain comfortable at all times.

Sleep Mode

Maximum comfort throughout the evening hours with the added benefit of energy savings. With Sleep Mode, the temperature gradually increases a few degrees over the evening.

Model Numbers	
Set Model Number	FFHP242ZQ2
Outdoor Unit Part Number	FFHP242ZQ2
Performance	
BTU (Cool)	28,000
BTU (Heat Pump)	28,400
Cooling Area (Sq. Ft.)	1,850
SEER (Air Conditioner)	16.0
HSPF (Heat Pump)	8.2
Inverter Technology	Yes
COP	2.9
Electrical	
Volts	230V/208V
Min Circuit Ampacity	20 A
Maximum Circuit Breaker	30 A
Rated Amps (Cool)	12.1
Rated Watts (Cool)	2,715
Rated Amps (Heat)	12.7
Rated Watts (Heat)	2,870
Features	
Controls	Ready-Select® Controls
Fan Speeds (Cool/Fan/Heat)	3/3/3
Low Voltage Start-Up	Yes
Turbo Fan	
Auto Fan	Yes
Energy Saver	
Sleep Mode	Yes
24-Hour On/Off Timer	Yes
Remote Control	Full-Function
Air CFM (High/Med/Low) Indoor	(588/471/412) 353
Air Direction Control (Vert./Horz.)	Swing/Manual
Air Discharge (Full-Width)	Bottom
Filter Type	Antimicrobial Mesh
Filter Access	Slide-Out
dB Indoor (High/Med/Low)	(57/54/48)
dB Outdoor	62
Warranty ¹	Yes
Included Accessories	
Drain Kit (Outdoor Unit)	Yes

¹ 1 yr Full / 5 yr sealed system



NOTE: For planning purposes only. Always consult local and national electric codes. Refer to Product Installation Guide for detailed installation instructions on the web at frigidaire.com.



Product Dimensions	
A - Height	31-1/8"
B - Width	38-5/8"
C - Depth	16-13/16"

All refrigeration and electrical work must be performed by a certified and licensed refrigeration technician for full parts and labor warranty validation. Insulated line sets and control wires are required and available for Frigidaire split systems in 25 ft. length. Each line set is equipped with flare nuts on both ends. Each system requires one line set for each indoor unit installed.

Accessories information available on the web at frigidaire.com

Multi-Zone Outdoor Condenser Submittal Sheet


FRIGIDAIRE

FFHP242ZQ2

Job: _____ Reference: _____ Construction: _____
 Location: _____ Approval: _____ Unit Number: _____
 Engineer: _____ Date: _____ Drawing Number: _____
 Submitted to: _____ Submitted by: _____

Power	
Min Circuit Ampacity	20 A
Maximum Circuit Breaker	30 A
Capacities	
Cooling	28,000 BTU
Cooling Watts	2,715 W
Min/Max Cooling	9,500 BTU/30,000 BTU
Heatpump Capacity (BTU)	28,400 BTU
HSPF	10.0
Outdoor Sound Rating	58 dB (A)
SEER	16.0
EER	10.3
Low Ambient Cooling	-5° - 110°F
Low Ambient Heating	5¢ 75
Voltage/Frequency/Phase	230/208/60Hz
Dehumidification	6.3 PT/H

Outdoor Unit	FFHP242ZQ2
Dimensions (H x W x D)	31-1/8" x 38-5/8" x 16-13/16"
Sound Rating	62 dB (A)
Net Weight	42 lb
Shipping Weight	58 lb
Fan Motor Load	.45 A
Drive Type	inverter
CFM (high)	4,000
Fan Type	Axial-flow
Fan Diameter/Number of Speeds	21-3/4"/1
Number of Poles and RPM	DC/830
Coil Type	aluminum fin & copper tube
Fin Type	coated fin
Pipe Type	copper internal thread
Fin Rows (FPI)	2
Tube Size	¢ 7.94 mm (5/16")
Features	
Controls	microprocessor
Remote Control	lcd wireless
Temperature Control	61-86°F (16-30°C)
Timer	24 hr
Air Louvers	2 pieces
Horizontal	manual
Vertical	swing
Low Voltage Restart	built-in
Self-Diagnosis	yes
Air Filter	washable, anti-mold
Refrigerant System	
Refrigerant	R410A
Ounces	84.66
Lineset	25 ft
Maximum Height	66 ft
Maximum Line Length	98 ft
Discharge Vapor Line (od)	6 mm (1/4")
Suction (od)	9 mm (5/8")
Operating Range	
Indoor Air Cooling Intake Temp Range	>= 61°F
Indoor Air Heating Intake Temp Range	<= 86°F
Outdoor Air Cooling Intake Temp Range	-5¢ 110°F
Outdoor Air Heating Intake Temp Range	-5¢ 75°F



FFHP242ZQ2 Outdoor

FRIGIDAIRE

USA • 10200 David Taylor Drive • Charlotte, NC 28262 • 1-800-FRIGIDAIRE • frigidaire.com
 CANADA • 5855 Terry Fox Way • Mississauga, ON L5V 3E4 • 1-800-265-8352 • frigidaire.ca

FFHP242ZQ2 07/18

© 2018 Electrolux Home Products, Inc.



Specifications
subject to change.