

Standard Flexible Couplings



Fernco's specially formulated PVC compound positively seals most sewer and drain connections.

Fernco makes the most complete line of couplings in the industry, from sizes 3/4" and larger. Custom large diameter couplings are available, along with shielded transitional couplings to ensure all pipes, underground and above-ground, can be connected with a Fernco coupling. Because Fernco couplings have earned a reputation for superior performance, you can have full confidence in their quality and reliability.

Tested designs backed by over five decades of proven experience

Available from 3/4" and larger

- Seals against infiltration and exfiltration
- Leak-proof, root-proof and resistant to many chemicals, ultra violet rays, fungus growth and normal sewer gas
- Conforms to ASTM D 5926, C 1173 and CSA B602
- Connects pipes of same or different materials and sizes
- Corrosion-resistant and rust-proof stainless steel clamps
- Made of elastomeric polyvinyl chloride (PVC)
- 4.3 PSI maximum test pressure
- 140°F maximum intermittent operating temperature
- 120°F maximum consistent operating temperature



High Torque Clamps

STANDARD on all 18" and larger couplings



Flexible Couplings

see sizes on pg. 17-24

1006 Series Couplings

Concrete to CI, Plastic, Copper, Steel or Lead

* Insert bushing included **Red** high torque clamps included

 new

10" x 10" (250 mm x 250 mm)	12.60 x 10.60 1006-1010	12.40 x 10.75 1006-1010RC	12.40 x 10.75 5006-1010RC*	
12" x 10" (300 mm x 250 mm)	16.29 x 10.75 1006-1210*	15.38 x 10.60 1006-1210RC*		15.38 x 10.60 1006-1210EB
12" x 10" (300 mm x 250 mm)	16.10 x 10.60 1006-1210LC*			
12" x 12" (300 mm x 300 mm)	16.29 x 12.39 1006-1212	15.25 x 12.60 1006-1212RC*	15.25 x 12.60 5006-1212RC*	15.38 x 12.60 1006-1212EB
12" x 12" LC (300 mm x 300 mm)	16.10 x 12.60 1006-1212LC*	16.10 x 12.60 1006-1212LCRC*	16.10 x 12.60 5006-1212LCRC*	16.10 x 12.60 1006-1212LCB*
15" x 10" (375 mm x 250 mm)	19.82 x 10.60 1006-1510*			
15" x 12" (375 mm x 300 mm)	19.82 x 12.60 1006-1512*	19.82 x 12.60 1006-1512RC*		19.70 x 12.60 1006-1512EB
15" x 15" (375 mm x 375 mm)	19.82 x 15.43 1006-1515	19.74 x 15.40 1006-1515RC*	19.74 x 15.40 5006-1515RC	
18" x 18" (450 mm x 450 mm)	22.50 x 18.90 1006-1818*	22.50 x 18.90 1006-1818RC*	22.50 x 18.90 5006-1818RC*	
21" x 21" (525 mm x 525 mm)	26.70 x 22.30 1006-2121*	26.70 x 22.30 1006-2121RC*		
24" x 24" (600 mm x 600 mm)	30.50 x 25.00 1006-2424*	30.50 x 25.00 1006-2424RC*		
27" x 27" (700 mm x 700 mm)	34.00 x 28.00 1006-2727*	34.00 x 28.00 1006-2727RC*	34.00 x 28.00 5006-2727RC*	

1051 Series Couplings

AC, DI to CI, Plastic, Copper, Steel or Lead

NOMINAL PIPE DIAMETER	STANDARD	STRONG BACK 1000 RC SERIES	STRONG BACK 5000 RC SERIES	ECCENTRIC
4" x 4" (100 mm x 100 mm)	4.80 x 4.53 1051-44	4.80 x 4.39 1051-44RC	4.80 x 4.39 5051-44RC	4.25 x 4.38 1051-44EB
4" x 6" (100 mm x 150 mm)	4.75 x 6.60 1051-46*	4.75 x 6.60 1051-46RC*	4.75 x 6.60 1051-46RC*	
5" x 4" (125 mm x 100 mm)	5.75 x 4.47 1051-54			6.00 x 4.38 1051-54EB
5" x 5" (125 mm x 125 mm)	6.05 x 5.54 1051-55	5.90 x 5.50 1051-55RC*		
6" x 4" (150 mm x 100 mm)	6.84 x 4.30 1051-64	6.95 x 4.38 1051-64RC*	6.95 x 4.38 5051-64RC*	6.95 x 4.38 1051-64EB
6" x 5" (150 mm x 125 mm)	6.81 x 5.17 1051-65	6.95 x 5.50 1051-65RC*		9.05 x 4.38 1051-65EB
6" x 6" (150 mm x 150 mm)	6.81 x 6.39 1051-66	6.96 x 6.60 1051-66RC	6.96 x 6.60 5051-66RC	
8" x 4" (200 mm x 100 mm)	9.12 x 4.38 1051-84*	9.12 x 4.50 1051-84RC*		9.05 x 4.38 1051-84EB
8" x 6" (200 mm x 150 mm)	9.12 x 6.38 1051-86*	9.12 x 6.38 1051-86RC*		9.05 x 6.38 1051-86EB
8" x 8" (200 mm x 200 mm)	9.12 x 8.49 1051-88	9.25 x 8.51 1051-88RC	9.25 x 8.51 5051-88RC	
10" x 8" (250 mm x 200 mm)	11.05 x 8.38 1051-10-8*	11.02 x 8.38 1051-10-8RC*		
10" x 10" (250 mm x 250 mm)	11.05 x 10.65 1051-1010	11.02 x 10.52 1051-1010RC	11.02 x 10.52 5051-1010RC	