

## HCC Holdings, Inc.

4700 West 160th  
Cleveland, Ohio 44135

Phone: 800-321-9532  
Website: www.Oatey.com



## STA PUT® Plumber's Putty

Date: August 2017

A plumbing sealing and caulking compound for setting plumbing fixtures, bowls, faucets, basin cocks, strainers, plugs, and sink frames. Will not stick to fingers or hands. Always the same smooth, uniform appearance from top to bottom of container with superior sealing qualities. **Sta put** will not harden, crumble, crack or shrink. It is flexible and stretchable, spreads easily, and can be molded into rings or shaped to the precise configuration needed. It provides a gas proof, fume proof, odor proof, insect proof and watertight seal. Meets or exceeds Federal Specification TT-P-1536.



## APPROVALS & LISTINGS

Meets Federal Specification TT-P-1536.

## SPECIFIC USES

Used for setting bowls, fixtures, faucets, basin cocks, strainers, plugs, sink frames as well as many other sealing and caulking jobs.

## SPECIFIC APPLICATIONS\*

Professional non-hardening putty for sealing and caulking.

\*For special applications which may not be covered on this or other Oatey literature, please contact Oatey Technical Services Department by phone 1-800-321-9532, or fax 1-800-321-9535, or visit our technical database web-site at [www.Oatey.com](http://www.Oatey.com).

## PHYSICAL PROPERTIES

Specific Gravity:	2.15 to 2.35
Solubility in water:	Insoluble
Appearance/color/odor:	Beige color with very mild vegetable oil odor

## DIRECTIONS FOR USE

Take out required amount and form the putty to the approximate shape needed. **Sta put** can be rolled between the palms of your hands to form a long cord-like shape. Lay out on the surface being sealed, overlapping the ends. Place the fixture over the bead, attach and tighten down the fasteners for the fixture. Enough **Sta put** should be used so that some excess putty is squeezed out from all around the fixture ensuring that a continuous seal has been made. Wipe off the excess; no additional sealer is needed. Use this method for setting bowls, fixtures, faucets, basin cocks, strainers, plugs, sink frames, toilet perimeters and other sealing and caulking applications.

## WARNINGS OR CAUTIONS

**DO NOT USE STA PUT IN DIRECT CONTACT WITH MARBLE, GRANITE OR OTHER POROUS STONE, CERAMICS OR MANUFACTURED SUBSTITUTES.**

Consult manufacturer. On natural materials (stone, marble, etc.), spray or brush contact area with clear acrylic lacquer and allow to dry. This prevents discoloration which might occur from putty components diffusing through the porous fixture. Then apply **Sta put**.

## MATERIAL SAFETY INFORMATION

**FOR MORE INFORMATION ON THIS PRODUCT, REQUEST SAFETY DATA SHEET (SDS) #1618E**

For Delivery By Fax	Call 1-800-321-9535
Internet	See SDS section of <a href="http://www.Oatey.com">www.Oatey.com</a>

This product is not classified as hazardous as defined by OSHA 29 CFR 1910.1200.

**HMIS® ratings** Health: 0  
 Flammability: 0  
 Physical hazard: 0

## SIZE & PACKING

STOCK NUMBER	SIZE	PACKING	WEIGHT/CASE
25101	14 oz.	24	22.9 lbs.
25103	3 lbs.	12	38.5 lbs.
25105	5 lbs.	6	32.0 lbs.
25110	7 lbs.*	6	45.0 lbs.

\*Plastic Pail with Handle