





Dimensions



Job Specifications



F-3000 Filtration System

Features

- Includes 1 replacement filter for use with InSinkErator water filtration system
- Replace every 6 months or if a noticeable reduction in flow rate occurs
- Compatible with InSinkerator F-3000, F-2000 or F-1000 Filter Replacements

Filters over 70 contaminants

- PFOA/PFOS
- Pharmaceuticals
- Lead/mercury
- · Herbicides/pesticides
- Solvent/glue/paint chemicals
- Cysts
- Volatile Organic Compounds (VOCs)
- Class 1 particulates (>0.5 micron)
- · Chlorine taste & odor

See Performance Data Sheet (PDS) for complete list of contaminants.

Certifications

- Products are Certified by one of both of industry-recognized agencies - NSF and IAPMO.
- NSF/ANSI 42/53
- NSF/ANSI 372 low lead
- · NSF/ANSI 58 reverse osmosis
- NSF/ANSI 401 pharmaceuticals, emerging contaminants

Specifications

Filter Capacity	500 gallons
Temperature Range	Incoming cold water supply line can be from 33°F to 100°F (1°C to 38°C). Connect to cold water supply line only.
Pressure	30-80 psi
Flow Rate	.75 gpm
Shipping Weight	Approximately 1.3 lbs.

Benefits

- Peace-of-mind for self, family and friends
- Assured of certified filtration reduction performance

Contact an authorized InSinkErator service agent for repairs or replacement components. Replacement filter F-3000 can be ordered by visiting shop.insinkerator.com or by contacting an authorized InSinkErator reseller.



The F-3000 filter is certified by IAPMO R&T against NSF/ANSI standards 42, 53, 401 and CSA B483.1 for the reduction of claims specified in the performance data sheet when used in system HWT300-F3000S. HWT300-F3000S is also certified against NSF/ANSI 58 for material safety requirement and NSF/ANSI 372 for Lead Free.



1-800-558-5700 www.insinkerator.com InSinkErator may make improvements and/or changes in the specifications at any time, in its sole discretion, without notice or obligation and further reserves the right to change or discontinue models.

®/TM © 2023 InSinkErator. All rights reserved.