

SPECIFICATION SUBMITTAL SHEET

j o n e s s t e p h e n s c o r p o r a t i o n

FLEXIBLE STAINLESS-STEEL PLUMBING CONNECTORS

features and benefits:

- Reliable, trouble-free service - Inner core of non-toxic polymer withstands temperatures of 33°F (1°C) to 174°F (86°C).
- Leak-proof seal - High quality outer braid of stainless steel and exclusive crimp-on fittings for maximum performance
- Quick and easy installation - No special tools; no soldering
- No pipe bending - Flexible connectors simplify installation-even in cramped spaces
- Pressure tested to 1100 PSI
- Chrome plated nut
- These products are NSF approved



FAUCET

| PART NO. | OD x FIP | LENGTH |
|----------|-------------|--------|
| S04-200 | 3/8" x 1/2" | 9 |
| S04-201 | 3/8" x 1/2" | 12 |
| S04-202 | 3/8" x 1/2" | 16 |
| S04-203 | 3/8" x 1/2" | 20 |
| S04-204 | 3/8" x 1/2" | 30 |
| S04-205 | 3/8" x 1/2" | 36 |
| S04-206 | 1/2" x 1/2" | 12 |
| S04-207 | 1/2" x 1/2" | 16 |
| S04-208 | 1/2" x 1/2" | 20 |
| S04-209 | 1/2" x 1/2" | 30 |
| S04-210 | 1/2" x 1/2" | 36 |

FAUCET

| PART NO. | FIP x FIP | LENGTH |
|----------|-------------|--------|
| S04-211 | 1/2" x 1/2" | 12 |
| S04-212 | 1/2" x 1/2" | 16 |
| S04-213 | 1/2" x 1/2" | 20 |
| S04-214 | 1/2" x 1/2" | 30 |
| S04-215 | 1/2" x 1/2" | 36 |

jones stephens corporation
3249 moody parkway • moody, alabama 35004
toll free phone: 1-800-355-6637 • toll free fax: 1-800-462-6991
www.plumbest.com