

INSTALLATION INSTRUCTIONS

P70084

THANK YOU FOR CHOOSING KALLISTA


We appreciate your commitment to Kallista quality products. Please take a moment to review this manual before you install your Kallista product. If you encounter any installation or performance problems, please do not hesitate to contact us at the phone number listed at the bottom of the page.

BEFORE YOU BEGIN

NOTE: For ease of installation, install the trip lever before installing toilet or tank.


- Prior to installation, unpack the trip lever and inspect it for damage. If the product is damaged, please contact Kallista immediately at the phone number listed at the bottom of the page.
- Observe all local plumbing and building codes.
- Kallista reserves the right to make revisions in the design of plumbing products without notice, as specified in the Price Book.

TOOLS AND MATERIALS



Pliers

INSTALL THE TRIP LEVER



INSTALLATION INSTRUCTIONS

P70084

INSTALL THE TRIP LEVER (cont'd)

- Remove the tank cover from the toilet.
- Insert the trip arm of the trip lever into the toilet tank hole. Ensure that the "UP" indicator on the trip lever escutcheon is pointing up (as shown).
- Install the spacer over the trip arm so the "UP" indicator on the spacer is pointing upward and is visible (as shown).
- Secure the trip lever assembly with the locknut. Note that the locknut has left-hand threads.
- Do not overtighten the locknut, or the trip lever will not move freely. If the assembly binds, loosen the locknut slightly until free movement is achieved.
- Hook the flapper ball chain to the hole in the trip arm. Check for proper chain length, and adjust as needed.
Note: The chain should have some slack in it when the trip lever is at rest.
- Check for smooth operation and flush actuation. Trip arm movement should be free of interference. The trip lever should be vertical when at rest.
- Replace the tank cover.