KALLISTA

Vir Stil_® Bathroom Sink Faucet

CODES/STANDARDS APPLICABLE FEATURES P24132 • Solid brass construction for durability and Specified model meets or exceeds the following: reliabilitv • ASME A112.18.1/CSA B125.1 ADA **CSA B651** OBC • Two-handle, widespread sink faucet for • NSF 61 8" (203 mm) - 16" (406 mm) centers EPA WaterSense® Quarter-turn washerless ceramic disc valves ADA* • Includes Soft Touch drain ICC/ANSI A117.1 • 1.2 gal/min (4.5 l/min) flow rate CSA B651* • Meets CalGreen requirements for bathroom OBC* (Lever Only) sink faucets All applicable US Federal and State material regulations • Complements the Vir Stil collection *Compliant when installed to the specific requirement of this regulation 8" (203 mm) Min 5-1/2" 16" (406 mm) Max (140 mm) **Handle Options** 3-1/16" Ø 2-1/8" (78 mm) (54 mm) 9-1/4" 3-1/16" (235 mm) 2-7/16" (78 mm) (62 mm) 4-7/8" (124 mm) Ø 2-1/8" (54 mm) Ø 1-1/8" 1-1/2" P24132-CR (38 mm) Max 2-1/8" 2-7/8" Ø 11/16" ò (54 mm) (73 mm) XXXXX |||| 3-1/16" 3-13/16" 2-7/16" (78 mm) (97 mm) (62 mm) Ø 1-7/16" 1/2"-14 NPSM 5-1/8" Ø 2-1/8" (130 mm) (54 mm) 1-1/4" OD P24132-LV Soft Touch Drain **INSTALLATION NOTES** Mounting Surface Hole Size. All dimensions are nominal. Spout Ø 13/16" (21 mm) Ø 1-5/16" (32 mm) Handles **Deck Thickness** Min Max 2-1/4" (57 mm) Spout ____ 1-1/2" (38 mm) Handles _ SPECIFIED MODEL Model Finishes Description Vir Stil Bathroom Sink Faucet, P24132-CR CP Polished Chrome AD Nickel Silver AG Brushed Nickel LB Bronze **Cross Handles** Vir Stil Bathroom Sink Faucet, LB Bronze

P24132-LV Vil Suit Balilloon Sink Paucet, Lever Handles AG Brushed Nickel

We reserve the right to make revisions without notice in the design of products or in packaging unless this right has specifically been waived at the time the order is accepted.

Questions? Problems? For additional assistance, please contact KALLISTA's Customer Service Department at 1-888-4-KALLISTA (1-888-452-5547) or kallista.com.