



Persuade® | K-4326

Elongated toilet bowl with skirted trapway

Features

- Elongated bowl offers added room and comfort
- Comfort Height® feature offers chair-height seating that makes sitting down and standing up easier for most adults
- Skirted trapway simplifies cleaning
- Combines with the K-3569 or K-19042 tank to create a complete K-6355 or K-75790 Persuade toilet
- Standard 12" (305 mm) rough-in only. Cannot be combined with K-5383, or K-5381 for use in 10" or 14" installations
- Patented ReadyLock® installation system, a simple solution for skirted toilets, saves time, hassle, and eliminates the need to drill into the floor for standard 12" (305 mm) rough-in
- 2" (51 mm) glazed trapway



Available Colors/Finishes

Color tiles intended for reference only.

0	White
96	Biscuit
NY	Dune
95	Ice Grey
7	Black Black



1-800-4KOHLER (1-800-456-4537)

Kohler Co. reserves the right to make revisions without notice to product specifications.

For the most current specification sheet, go to www.kohler.com USA or www.kohler.ca Canada.

7-06-2026 22:03 - US-CA

THE BOLD LOOK
OF **KOHLER**

Codes/Standards

Accessibility standards may require controls to be located on the open side of the toilet.

Plumbing codes may require elongated toilets and elongated, open-front seats in public bathrooms.

ASME A112.19.2/CSA B45.1

ASME A112.19.14

DOE - Energy Policy Act 1992

Technical Information

Rough-in:	Standard 12" (305mm)
Flush Type:	Class Five
Bowl Shape:	Elongated
Seat-Mounting Holes:	5-1/2" (140 mm)
Waste Outlet:	Floor
Trapway Size:	2" (51 mm)
Trapway Type:	Skirted
Water Surface Size:	4-1/2" x 5-3/4" (114 mm x 146 mm)

Recommended Products/Accessories

K-23726 Drain treatment

K-3569 Toilet tank, dual-flush

K-19042 Toilet tank, dual-flush

Warranty

See website for detailed warranty information.

KOHLER® Toilets and Seats Limited Warranty



No image available.
This product is a component and not intended to be a standalone installation.

Installation

- Seat sold separately
- Standard 12" (305 mm) rough-in

Installation Notes

Install this product according to the installation instructions.

Product dimensions are nominal and may vary per ASME
A112.19.2 tolerances.

