

# Archer® 5' VibrAcoustic® Bath K-1122-VBW

#### **Features**

- VibrAcoustic calms and soothes with sound vibration technology.
- Six concealed speakers send sound waves through the water to gently massage the body.
- Four original instrumental compositions offer different levels of relaxation.
- Syncs with devices enabled with BLUETOOTH® wireless technology including smartphones, MP3 players, tablets, and laptops located up to 33 feet away.\*
- Customize your experience with the high-resolution color touch screen
- Fully adjustable volume above and below the water.
- Functions as a hydrotherapy bath when full of water and a stereo system when empty.
- Bask® heated surface creates spa-like relaxation with soothing warmth on your back and neck.
- Three heat settings allow you to customize the surface temperature.
- Comfort Depth® design offers a convenient 19-inch step-over height while retaining the same depth as a standard 21-inch bath.
- Molded lumbar support and armrests offer extra comfort while bathing.
- Slotted overflow allows for deep soaking.
- Textured bottom surface.
- Reversible drain.
- Includes 25 feet of wiring and amplifier.

#### Material

Acrylic

#### **Hydrotherapy**

VibrAcoustic

#### Installation

- Drop-in
- Requires 110V electrical service.

#### **Additional Hydrotherapy Options**

- Soaking Bath K-1123-0
- Soaking Bath + Bask heated surface K-1123-W1
- BubbleMassage air bath K-1122-G
- BubbleMassage air bath + Bask heated surface K-1122-GW
- VibrAcoustic K-1122-VB
- VibrAcoustic + Bask heated surface K-1122-VBW
- Whirlpool K-1122-0
- Whirlpool + heater K-1122-H
- Whirlpool + Bask heated surface K-1122-W1
- Whirlpool + BubbleMassage air bath K-1122-XHG



ADA

#### Codes/Standards

ASME A112.19.7/CSA B45.10 CSA B45.5/IAPMO Z124 ASTM E162 ASTM E662 UL 1795 ADA ICC/ANSI A117.1

# **KOHLER® Plastic Baths and Receptors Lifetime Limited Warranty**

See website for detailed warranty information.

The BLUETOOTH® word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. and any use of such marks by Kohler Co. is under license. Other trademarks and trade names are those of their respective owners.

#### Available Colors/Finishes

Color tiles intended for reference only.

Color	Code	Description
	0	White
	96	Biscuit
	47	Almond
	NY	Dune
	95	Ice™ Grey
100	G9	Sandbar
	K4	Cashmere
	58	Thunder™ Grey
435	7	Black Black™






### **Archer®**

## 5' VibrAcoustic® Bath

#### K-1122-VBW



#### **Required Electrical Service**

One circuit required, protected with Class A Ground-Fault Circuit-Interrupter (GFCI). Outside North America, this device may be known as a Residual Current Device (RCD).

(105 mm)

Amplifier, Heated

Bath Drain

120 V, 15 A, 50/60 Hz

Surface:

#### **Technical Information**

All product dimensions are nominal.

Installation: Drop-in Drain location: End

Basin area, bottom: 45-1/8" x 19-11/16" (1146 mm x 500 mm) Basin area, top: 52-3/4" x 25-5/16" (1340 mm x 643 mm)

Weight: 86 lbs (39 kg)

Minimum floor load: 44 lbs/ft<sup>2</sup> (214.8 kg/m<sup>2</sup>)

Water depth: 15" (381 mm)
Water capacity: 58 gal (219.6 L)

Cutout: Drop-in, 58-1/2" x 30-1/2" (1486 mm x

775 mm)

Electrical component Amplifier: 120 V, 1.1 A, 50/60 Hz

rating: Heated Surface: 120 V, 0.5 A, 50/60 Hz,

65 W

#### **Notes**

Interface Location

Measure your actual product for rough-in details. Install this product according to the installation instructions.

The hot water supply should be 70% of the capacity of the bath or greater. Installations will vary.

Control amplifier fits 16" (406 mm) center studs. 25' (7.6 m) cables are included.

ADA compliant when installed to the specific requirements of these regulations.



Kohler Co. reserves the right to make revisions without notice to product specifications. For the most current Specification Sheet, go to <a href="https://www.kohler.com">www.kohler.com</a>. 9-7-2019 05:27 - US/CA

