# **Archer®**



72" x 36" alcove Heated BubbleMassage™ air bath and whirlpool, right drain

**K-1124-XGHRA** 

#### **Features**

- 118 airjets release thousands of heated bubbles that surround and support the body in a warm massage
- Automatic and manual purge cycles remove residual water from air channels after use
- Variable-speed blower lets you adjust Heated BubbleMassage™ massage intensity to 18 levels
- Single-speed whirlpool revitalizes sore muscles
- 8 fully adjustable whirlpool jets allow users to customize hydromassage flow and direction at each jet
- Comfort Depth® design offers a convenient 19" step-over height while retaining the same depth as a standard 21" bath
- Integral lumbar support
- Slotted overflow allows for deep soaking
- Integral apron
- Integral flange helps prevent water from seeping behind wall and simplifies alcove installation
- Textured bottom surface
- Coordinates with other products in the Archer collection
- Built-in 600W BubbleMassage™ heater warms humidified air before it enters the bath
- Automatic and manual purge cycles remove residual water from air channels after use

### Material

Acrylic

### **Hydrotherapy**

Whirlpool

#### Technology

- Auto-shutoff timer on blower allows users to enjoy Heated BubbleMassage™ experience for 60 minutes before turning
- User interface: electronic keypad control for Heated BubbleMassage™; air switch actuator for whirlpool

### Installation

Right drain

### Required Products/Accessories

K-7271 Brass Slotted Overflow Bath Drain

or

K-7272 PVC Slotted Overflow Bath Drain

### Recommended Products/Accessories

K-23726 Drain treatment



# ADA

### Codes/Standards

ASME A112.19.7/CSA B45.10 CSA B45.5/IAPMO Z124 ASTM E162

ASTM E662

UL 1795

CSA C22.2 No. 218.2

ADA

ICC/ANSI A117.1

cUL Listed

UL Listed

## **KOHLER® Plastic Baths and** Shower Bases Lifetime Limited WarrantyKOHLER® Hydrotherapy **Components Five-Year Limited** Warrantv

See website for detailed warranty information.

### Available Colors/Finishes

Color tiles intended for reference only.

Color	Code	Description
	0	White
	96	Biscuit
	NY	Dune
	95	Ice™ Grey
	58	Thunder™ Grey
	7	Black Black™








72" x 36" alcove Heated BubbleMassage™ air bath and whirlpool, right drain

**K-1124-XGHRA** 



## **Required Electrical Service**

Three dedicated circuits required, protected with Class A Ground-Fault Circuit-Interrupter (GFCI). Outside North America, this device may be known as a Residual Current Device (RCD).

Pump, Heater: 120 V, 15 A, 60 Hz 120 V, 15 A, 60 Hz Heater: Blower: 120 V, 15 A, 60 Hz

### **Technical Information**

All product dimensions are nominal.

Drain location: Right

Basin area, bottom: 51-3/8" x 21" (1305 mm x 533 mm) 64-1/2" x 30-1/2" (1638 mm x 775 mm) Basin area, top:

Weight: 165 lbs (74.8 kg)

44.2 lbs/ft<sup>2</sup> (215.8 kg/m<sup>2</sup>) Minimum floor load:

Water depth: 15" (381 mm) Water capacity: 72 gal (272.5 L)

Electrical component Pump: 120 V, 7 A, 60 Hz Heater: 120 V, 5 A, 60 Hz rating:

> Heater: 120 V, 12 A, 60 Hz Blower: 120 V. 10 A. 60 Hz

#### **Notes**


Measure your actual product for rough-in details.

Install this product according to the installation instructions.

The hot water supply should be 70% of the capacity of the bath or greater. Installations will vary.

Remote blower installation kit is available for relocating the blower. Provide access for servicing the blower.

Do not relocate or alter the PVC tee or coiled flexible tubing connected to the blower. Follow the blower relocation instructions exactly. ADA compliant when installed to the specific requirements of these regulations.



Kohler Co. reserves the right to make revisions without notice to product specifications. For the most current Specification Sheet, go to www.kohler.com USA or www.kohler.ca Canada 10-22-2025 13:15 - US/CA

