# Mach Flex™

**KOHLER** Faucets Touchless toilet flushometer conversion kit, Cortex™compatible, DC-powered, 1.6 apf K-11TH00R10-CK

#### **Features**

- Converts Mach® Tripoint® and Mach® WAVE flush valves into Mach Flex™ flush valves
- 1.6 gpf (6.0 lpf)
- Activation distance, arming time, flush delay, and several other parameters can be adjusted by approved tech professionals using Cortex™ mobile app
- Adjustable automatic sentinel flush keeps trapway fresh while saving water
- Long-lasting energy cell to prevent frequent battery replacement
- Box includes: Sensor cap, long-lasting energy cell

## Material

Durable brass construction

## Technology

- Flex sensing technology provides accurate activation and flexible adjustability of several different parameters by approved tech professionals using Cortex™ mobile app or Cortex-connected ecosystem
- Connects wirelessly to KOHLER® commercial connected systems (sold separately), or by approved tech professionals to Cortex™ mobile app for individual adjustment. Please contact info@kohlercortex.com for more information



**CSA B651** ADA OBC

## Codes/Standards

ASSE 1037/ASME A112.1037/CSA B125.37 ADA ICC/ANSI A117.1 **CSA B651** OBC

## **KOHLER® One-Year Limited** Warranty

See website for detailed warranty information.

The BLUETOOTH® word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. and any use of such marks by Kohler Co. is under license. Other trademarks and trade names are those of their respective owners.

### Available Colors/Finishes

Color tiles intended for reference only.

Color Code Description


CP Polished Chrome





# Mach Flex™



**KOHLER** Faucets Touchless toilet flushometer conversion kit, Cortex™compatible, DC-powered, 1.6 gpf K-11TH00R10-CK







## **Technical Information**

All product dimensions are nominal.

Battery - DC, included Power source:

Spout:

Bluetooth® range: 30 ft (9.1 m)

Bluetooth® version: 4.2

#### **Notes**

Install this product according to the installation

ADA, OBC, CSA B651 compliant when installed to the specific requirements of these regulations.

