

# **Devonshire®**

5' BubbleMassage™ Bath K-1357-GRAW

#### **Features**

- Bask® heated surface creates spa-like relaxation with soothing warmth on your back and neck.
- Three heat settings allow you to customize the surface temperature.
- 120 airjets release thousands of bubbles that surround, support, and massage the body.
- Variable-speed blower lets you adjust massage intensity to 18 levels.
- Molded lumbar support and armrests offer extra comfort while bathing.
- Integral apron.
- Integral flange helps prevent water from seeping behind wall and simplifies alcove installation.
- Textured bottom surface
- Immediate and manual purge cycles remove residual water from air channels after use.
- Right-hand drain.

#### Material

Acrylic

## **Hydrotherapy**

BubbleMassage

### Installation

Three-wall alcove.

### **Additional Hydrotherapy Options**

- Soaking Bath K-1184-RA
- Soaking Bath + Bask heated surface K-1184-RAW
- BubbleMassage air bath K-1357-GRA
- BubbleMassage air bath + Bask heated surface K-1357-GRAW
- VibrAcoustic K-1357-VBRA
- VibrAcoustic + Bask heated surface K-1357-VBRAW
- Whirlpool K-1357-RA
- Whirlpool + Bask heated surface K-1357-RAW
- Whirlpool + heater K-1357-HR

### **Recommended Products/Accessories**

K-1446 Remote Installation Kit K-7161-AF Bath Drain K-24916 Wireless Music Kit K-37380 30" Rough-in Cable Bath Drain K-37383 30" Rough-in Cable Bath Drain



### Codes/Standards

ASME A112.19.7/CSA B45.10 CSA B45.5/IAPMO Z124 ASTM E162 ASTM E662 UL 1795 CSA C22.2 No. 218.2

# KOHLER® Plastic Baths and Receptors Lifetime Limited Warranty KOHLER® Hydrotherapy Components Five-Year Limited Warranty

See website for detailed warranty information.

### **Available Colors/Finishes**

Color tiles intended for reference only.

Color	Code	Description
	0	White
	96	Biscuit
	47	Almond
	NY	Dune
1000	G9	Sandbar








# **Devonshire®**


# 5' BubbleMassage™ Bath K-1357-GRAW

No change in measurements if connected with drain illustrated. (K-7161-AF)









### **Required Electrical Service**

One circuit required, protected with Class A Ground-Fault Circuit-Interrupter (GFCI). Outside North America, this device may be known as a Residual Current Device (RCD).

Blower, Heated Surface:

120 V, 15 A, 60 Hz

#### **Technical Information**

All product dimensions are nominal.

Three-wall alcove Installation:

Right Drain location:

Basin area, bottom: 42" x 20" (1067 mm x 508 mm) Basin area, top: 51" x 24" (1295 mm x 610 mm)

Weight: 104 lbs (47.2 kg) Minimum floor load: 47 lbs/ft<sup>2</sup> (229.5 kg/m<sup>2</sup>) Water depth: 14-1/2" (368 mm) Water capacity: 60 gal (227.1 L)

Electrical component Blower: 120 V, 10 A, 60 Hz

Heated Surface: 120 V, 0.5 A, 60 Hz, 65 rating:

Minimum flat for door: 2-1/2" (64 mm)

#### **Notes**

Measure your actual product for rough-in details. Install this product according to the installation instructions.

The hot water supply should be 70% of the capacity of the bath or greater. Installations will vary.

Remote blower installation kit K-1446 is available for relocating the blower. Provide access for servicing the blower.

Do not relocate or alter the PVC tee or coiled flexible tubing connected to the blower. Follow the blower relocation instructions exactly.



For the most current Specification Sheet, go to www.kohler.com.



9-7-2019 06:41 - US/CA