

## Features

- Robust steel tube frame.
- Insulated tank to prevent sweating.
- Large flush actuator plate opening can be removed for easy access to inner tank.
- Adjustable height allows bowl to be set anywhere from 15" to 23" (381 to 584 mm) from floor.
- Dual-flush actuator offers a choice of 0.8 or 1.6 gpf (3.0 or 6.0 lpf).
- Requires K-76395 Veil Intelligent wall-hung toilet (sold separately).

## Technology

- Dual-flush technology allows you to choose between a full or partial flush.

## Installation

- Durable steel frame carrier is installed on 2"x6" studs behind the wall. See installation guide and installation video for more detailed information.
- When installed per KOHLER's installation instructions, the KOHLER in-wall tank and carrier system can support up to 880 lbs. without damage.
- Supply line sold separately.

## Water Conservation & Rebates

- Eligible for consumer rebates in some municipalities.

## Required Products/Accessories

K-76395 Wall-hung dual-flush intelligent toilet



ADA

CSA B651

OBC

## Codes/Standards

ASME A112.6.2  
ASME A112.19.14  
ADA  
ICC/ANSI A117.1  
CSA B651  
OBC

## KOHLER® Intelligent Toilet and C3® Cleansing Seat Three-Year Limited Warranty

See website for detailed warranty information.

No image available.  
This product is a component and not intended to be a standalone installation.

### Technical Information

All product dimensions are nominal.

Toilet type:	In-wall tank, Wall-mount In-wall mount
Waste Outlet:	Wall
Flush type:	Gravity washdown
Water Consumption	
Full:	1.6 gpf (6 lpf)
Reduced:	0.8 gpf (3 lpf)

### Notes

Install this product according to the installation instructions.

ADA, OBC, CSA B651 compliant when installed to the specific requirements of these regulations.

Plumbing codes may require elongated toilets and elongated, open-front seats in public bathrooms.

Accessibility standards may require controls to be located on the open side of the toilet.