



Brenham™

Wall-mount Bathroom Sink With Shroud

K-1999-8

Features

- 8" (203 mm) widespread faucet holes
- Oval basin
- Overflow drain
- Includes wall hanger
- Combination consists of the K-1997-8 basin and the K-1998 shroud

Material

- Vitreous china

Installation

- Wall-mount
- Drilled for concealed arm carrier installation

Recommended Products/Accessories

K-23726 Drain treatment
K-23725 Cast iron cleaner

Optional Products/Accessories

K-8998 P-Trap

Included Components

K-1997-8 Wall-Mount Bathroom Sink
K-1998 Shroud



ADA	CSA B651	OBC
-----	----------	-----

Codes/Standards

ASME A112.19.2/CSA B45.1
ADA
ICC/ANSI A117.1
CSA B651
OBC

KOHLER® Vitreous China Bathroom Sink Lifetime Limited Warranty


See website for detailed warranty information.

Available Colors/Finishes

Color tiles intended for reference only.

Color	Code	Description
-------	------	-------------

	0	White
---	---	-------



Technical drawing of the 1000 Series Locking Device, showing top and side views with dimensions in inches and millimeters.

Top View Dimensions:

- Overall Width: 18-5/16" (465 mm)
- Overall Height: 19-3/4" (502 mm)
- Top Flange Thickness: 2-11/16" (68 mm)
- Distance from Top Flange to Center: 7-15/16" (202 mm)
- Distance from Top Flange to Side Mounting Hole: 8-9/16" (217 mm)
- Distance from Top Flange to Locking Device Holes: 3-5/16" (84 mm)
- Leveling Screw Hole Diameter: Ø 1-1/4" (32 mm)
- Locking Device Holes Diameter: Ø 1-3/16" (30 mm)

Side View Dimensions:

- Overall Height: 31" (787 mm)
- Top Flange Thickness: 9/16" (14 mm)
- Distance from Top Flange to Locking Device: 4" (102 mm)
- Locking Device Width: 9-1/4" (235 mm)
- Locking Device Height: 6" (152 mm)
- Distance from Locking Device to Side Mounting Hole: 2-5/8" (67 mm)
- Distance from Locking Device to Side Mounting Hole: 6-1/2" (165 mm)
- Distance from Locking Device to Side Mounting Hole: 9-3/4" (248 mm)
- Distance from Locking Device to Side Mounting Hole: 28-1/2" (724 mm)
- Distance from Locking Device to Side Mounting Hole: 29-1/8" (740 mm)
- Side Mounting Hole Diameter: Ø 5/16" (8 mm)
- Side Mounting Hole Depth: 3/8" (9.5 mm)
- Side Mounting Hole Diameter: 1-1/4" OD
- Side Mounting Hole Depth: 3/8" Cold
- Side Mounting Hole Depth: 3-1/2" (89 mm)
- Side Mounting Hole Depth: 4" (102 mm)

	ADA and TAS	Children's Environment ADA and TAS Ages 6-12 yrs
A	34" (864 mm)	31" (787 mm)
B	27" (686 mm)	24" (610 mm)
C	11" (279 mm)	11-1/16" (281 mm)
D	9" (229 mm)	9-1/16" (230 mm)
E	8" (203 mm)	8-1/16" (205 mm)

Basin configuration:	Single Bowl
Center(s):	8" (203 mm)
Bowl area:	Length: 14-3/8" (365 mm) Width: 12-5/16" (313 mm) Water depth: 3-1/4" (83 mm)
With overflow:	Yes
Number of deck holes:	3
Faucet hole(s):	1-3/8" (35 mm)
Drain hole:	1-3/4" (44 mm)

ADA, OBC, CSA B651 compliant when installed to the specific requirements of these regulations.