## **Sunstruck®**



60-1/2" x 34-1/2" freestanding Heated BubbleMassage™ air bath with straight shroud K-24008-GH

#### **Features**

- 118 to 122 airjets release thousands of heated bubbles that surround and support the body in a warm massage
- Automatic and manual purge cycles remove residual water from air channels after use
- Variable-speed blower lets you adjust massage intensity to 18 levels
- Freestanding design creates a striking focal point in your bathing area
- 16" (406 mm) depth offers a deep soaking experience
- Integral lumbar support on both ends
- Textured bottom surface
- Wide ledge on one side is ideal for deck-mount faucet and/or handshower
- Straight shroud
- Built-in 600W BubbleMassage™ heater warms humidified air before it enters the bath
- Automatic and manual purge cycles remove residual water from air channels after use

#### Material

Acrylic

#### **Technology**

- Auto-shutoff timer on blower allows users to enjoy Heated BubbleMassage™ experience for 60 minutes before turning
- User interface: electronic keypad control

### Installation

- Center drain
- PureFlo drains are not recommended for a deck-mount faucet installation
- Remote blower motor installation required (relocation kit is included)

#### **Required Products/Accessories**

K-T37391 Rotary-turn bath drain trim K-T37392 Rotary-turn bath drain trim

or

K-78438 30" cable bath drain

#### **Recommended Products/Accessories**

K-7265 Brass toe tap bath drain K-23726 Drain treatment



#### Codes/Standards

ASME A112.19.7/CSA B45.10 CSA B45.5/IAPMO Z124 ASTM E162 ASTM E662 UL 1795 CSA C22.2 No. 218.2 cUL Listed UL Listed

# KOHLER® Plastic Baths and Shower Bases Lifetime Limited WarrantyKOHLER® Hydrotherapy Components Five-Year Limited Warranty

See website for detailed warranty information.

#### **Available Colors/Finishes**

Color tiles intended for reference only.

**Color Code Description** 

0 White



# **Sunstruck®**



60-1/2" x 34-1/2" freestanding Heated BubbleMassage™ air bath with straight shroud K-24008-GH

No change in measurements if connected with drain illustrated. (K-37386) 4-3/16" Recommended Faucet Location (102 mm) (102 mm) (106 mm) −30-5/16" (770 mm)− (76 mm) 18-5/16" Recommended Faucet Hole Location (465 mm) 5-11/16"  $(144 \text{ mm})_{-}$ -60-9/16" (1538 mm) Lumbar (102 mm) -34-11/16" (881 mm)-Angle 19° 25-5/8" 17-11/16" (651 mm) (449 mm) 7/16" (11 mm) -57-1/8" (1451 mm) 3-5/16" (84 mm) 16-7/16" (418 mm) -30-13/16" (783 mm) -

## **Required Electrical Service**

Two dedicated circuits required, protected with Class A Ground-Fault Circuit-Interrupter (GFCI). Outside North America, this device may be known as a Residual Current Device (RCD).

Blower: 120 V, 15 A, 60 Hz Heater: 120 V, 15 A, 60 Hz

#### **Technical Information**

All product dimensions are nominal.

Drain location: Center

Basin area, bottom: 39-5/8" x 23-5/8" (1006 mm x 599 mm) Basin area, top: 49-1/2" x 25-1/2" (1257 mm x 648 mm)

Weight: 130 lbs (59 kg)

Minimum floor load: 50 lbs/ft<sup>2</sup> (244.1 kg/m<sup>2</sup>)

Water depth: 16" (406 mm)
Water capacity: 60 gal (227.1 L)

Template: Footprint, 1364287, not required, not

included

Electrical component Blower: 120 V, 10 A, 60 Hz rating: Heater: 120 V, 5 A, 60 Hz

#### **Notes**

Measure your actual product for rough-in details.

Install this product according to the installation instructions.

The hot water supply should be 70% of the capacity of the bath or greater. Installations will vary.

If installing a rim-mount faucet, make sure there is no interference above or below the deck before drilling any holes.



Kohler Co. reserves the right to make revisions without notice to product specifications. For the most current Specification Sheet, go to <a href="https://www.kohler.com">www.kohler.com</a> USA or <a href="https://www.kohler.com">www.kohler.ca</a> Canada 9-19-2025 08:29 - US/CA

