



# 71-3/4" H pivot shower door with 3/8"-thick glass **K-27607-10L**

#### **Features**

- Frameless design emphasizes glass and creates a sleek, minimalist look
- Full-length magnetic seal keeps door firmly closed, providing excellent water containment
- Innovative L- bracket secures the fixed panel in place and gives it a sturdy feel while also being unobtrusive to the showering space
- Continuous 7/8" (22 mm) high aluminum bottom threshold
- Back-to-back 11-3/16" (284 mm) vertical shower door pulls
- Coordinates with other products in the Components collection
- CleanCoat®+ glass coating creates a hydrophobic barrier that repels water, soap scum, and residue, saving time and protecting shower doors 10 times longer than original CleanCoat. (Based on 2021 internal wear/abrasion testing using a microfiber cloth.)

### Material

- Frameless, 3/8" (10 mm) thick Crystal Clear tempered glass
- Anodized aluminum prevents rust and corrosion

## Installation

- Fits opening widths 46"–46-3/4" (1168–1187 mm)
- 3/4" (19 mm) width adjustment
- Out-of-plumb adjustability simplifies installation
- Door can be installed to open to the left or right to suit your bathroom layout
- For residential use only
- Not for use in hospitality

## **Included Components**

27715-10L 3/8" pivot door glass and hardware, no handle K-27679 11" shower door handle



## Codes/Standards

ANSI Z97.1 CAN/CGSB-12.1 CPSC 16CFR 1201

## **KOHLER® Bath and Shower Doors Ten-Year Limited Warranty**

See website for detailed warranty information.

## **Available Colors/Finishes**

Color tiles intended for reference only.

Color	Code	Description
	SHP	Bright Polished Silver
	BL	Matte Black
600	BNK	Anodized Brushed Nickel

## Available Glass Options Code Description


L Crystal Clear







# 71-3/4" H pivot shower door with 3/8"-thick glass **K-27607-10L**



## **Technical Information**

All product dimensions are nominal.

Base-To-Wall 1/4" (6 mm)

Radius - Max:

Shower Ledge Min 3/4" (19 mm)

Flat:

Shower Wall Min 5-1/2" (140 mm)

Flat:

Wall Studs Required Yes

for Door:

### **Notes**

Install this product according to the installation instructions.

The vertical opening should be a minimum of 73-1/2" (1867 mm) to allow for installation clearance.

