

Features

- For use with the K-29638 Aquifer®+ water filtration system
- Hollow fiber membrane technology reduces bacteria and virus in the water
- 0.85 gpm maximum flow rate at 60 psi
- Filter head automatically turns off water supply when cartridge is removed
- Also sold together with K-77687 as K-29651 Aquifer®+ replacement filter cartridge two-pack

Material

- High-impact plastic construction

Installation

- Under-sink
- Quarter-turn twist cartridge for easy installation and replacement
- For cold water use only





Codes/Standards

CSA B483.1
NSF/ANSI 42
NSF/ANSI 53
NSF/ANSI 401
NSF Protocol P231
NSF Protocol P473

KOHLER® One-Year Limited Warranty

See website for detailed warranty information.



Technical Information

All product dimensions are nominal.

Faucet flow rate: 0.85 gal/min (3.2 l/min)

Spout:

Pressure/fixture Supply Requirements

Fixture pressure 120 psi (827.4 kPa)
max (static):

Fixture pressure min 40 psi (275.8 kPa)
(static):

Notes

Install this product according to the installation instructions.

To prevent the risk of property damage, protect from freezing.

For cold water use only.

To ensure the filter continues to reduce contaminants effectively, it is recommended that the filter gets replaced every 6 months.

Application guideline/water supply parameters:

Water Pressure: 40-120 psi (276-827 kPa)

Water Temperature: 33-100°F (0.5-37.8°C)

Capacity: 389 gal (1,472 L)