

## Elate® Single-function showerhead, 1.5 gpm K-33641-H

#### Features

- Full coverage spray produces an encompassing spray ideal for everyday use
- 1.5 gpm (5.7 lpm) maximum flow rate at 45 psi (3.1 bar)
- MasterClean<sup>™</sup> sprayface features an easy-to-clean surface that withstands mineral buildup and maximizes spray performance
- Coordinates with other products in the Elate collection
- This product can help a building earn Water Efficiency points in LEED® Green Building Rating System

#### Material

- Durable material construction
- KOHLER finishes resist corrosion and tarnishing

### Installation

- Wall-mount
- 1/2" -14 NPT connection
- Shower arm and flange sold separately





**Codes/Standards** ASME A112.18.1/CSA B125.1 DOE - Energy Policy Act 1992 EPA WaterSense® California Energy Commission (CEC)

## KOHLER<sup>®</sup> Faucet Lifetime Limited Warranty

See website for detailed warranty information.

## Available Colors/Finishes

Color tiles intended for reference only.

#### Color Code Description


- CP Polished Chrome
- BN Vibrant® Brushed Nickel
- BL Matte Black
- 2MB Vibrant® Brushed Moderne Brass




## **Elate**®

# KOHLER, Faucets

Single-function showerhead, 1.5 gpm K-33641-H





### **Technical Information**

All product dimensions are nominal	
Drain included: No	
Spout:	
Handshower rated max flow:	1.5 gal/min (5.7 l/min)
Shower/Rainhead rated max flow:	1.5 gal/min (5.7 l/min)

#### Notes

Install this product according to the installation instructions.

