



# Highline®

Two-piece elongated toilet, 1.28 gpf  
**K-37740**

## Features

- Two-piece design
- Elongated bowl offers added room and comfort
- Comfort Height® feature offers chair-height seating that makes sitting down and standing up easier for most adults
- 1.28 gpf (4.8 lpf)
- Left-hand Polished Chrome trip lever
- 2-1/4" (57 mm) fully glazed trapway
- Equipped with Sloan FLUSHMATE® – Sloan® Valve Company

## Installation

- Standard 12" (305 mm) rough-in
- Seat and supply line sold separately

## Recommended Products/Accessories

- K-4650 Lustra™ Elongated toilet seat
- K-4650-A Lustra™ Elongated toilet seat with antimicrobial agent
- K-5420 Low-Profile Bolt Caps

## Included Components

- K-4304 Elongated toilet bowl
- K-37920 Toilet tank, 1.28 gpf



**ADA** **CSA B651** **OBC**

## Codes/Standards

ASME A112.19.2/CSA B45.1  
DOE - Energy Policy Act 1992  
EPA WaterSense®  
California Energy Commission (CEC)  
ADA  
ICC/ANSI A117.1  
CSA B651  
OBC

## KOHLER® One-Year Limited Warranty

See website for detailed warranty information.

## Available Colors/Finishes

*Color tiles intended for reference only.*

| Color                                                                               | Code | Description  |
|-------------------------------------------------------------------------------------|------|--------------|
|  | 0    | White        |
|  | 96   | Biscuit      |
|  | 7    | Black Black™ |

1-800-4KOHLER (1-800-456-4537)

Kohler Co. reserves the right to make revisions without notice to product specifications.

For the most current Specification Sheet, go to [www.kohler.com](http://www.kohler.com) USA or [www.kohler.ca](http://www.kohler.ca) Canada

10-6-2025 20:20 - US/CA

THE BOLD LOOK  
OF **KOHLER®**

**Highline®**  
Two-piece elongated toilet, 1.28 gpf  
**K-37740**



|                       |                 |
|-----------------------|-----------------|
| Toilet type:          | Floor-mount     |
| Waste Outlet:         | Floor           |
| Flush type:           | Pressure Lite   |
| Trap passageway:      | 2-3/16" (55 mm) |
| Rim to water surface: | 5-3/4" (146 mm) |
| Rough-in:             | 12" (305 mm)    |

## Fixture Supply Requirements

Min static pressure: 35 psi (241.3 kPa)  
Max static pressure: 80 psi (551.6 kPa)

## Notes

Install this product according to the installation instructions.

Product dimensions are nominal and may vary per ASME A112.19.2 tolerances.

ADA, OBC, CSA B651 compliant when installed to the specific requirements of these regulations.

Plumbing codes may require elongated toilets and elongated, open-front seats in public bathrooms.

Accessibility standards may require controls to be located on the open side of the toilet.