

Cimarron® Toilet Tank K-5692

Features

- Flush is activated by a no-touch sensor mounted inside the tank
- Powered by 4 AA batteries (included).
- 1.28 gallons per flush (gpf).
- When batteries are low, the unit will beep five times at half-second intervals when activated to indicate it's time to replace them.
- Combines with the K-4309 bowl to create a complete K-6418 Cimarron toilet.
- Coordinates with other products in the Cimarron collection.
- Touchless has no impact on water usage.

Technology

- Touchless module projects a field through the top of the tank lid that senses your hand, causing the toilet to flush.
- Single-flush gravity uses the force of gravity and a precision-engineered tank, bowl, and trapway to create a strong siphon during flushing.
- AquaPiston canister allows water to flow into the bowl from all sides (360 degrees), increasing the power and effectiveness of the flush.
- Flush valve's 3:2 ratio harnesses the natural force of gravity and optimizes flush performance.
- Durable canister design has 90% less exposed seal material than a 3-inch flapper, for leak-free performance.
- Light-touch canister flush requires a lower actuation force than a flapper.

Recommended Products/Accessories

K-4309 Elongated Toilet Bowl



Codes/Standards

ASME A112.19.2/CSA B45.1

KOHLER® One-Year Limited Warranty

See website for detailed warranty information.

Available Colors/Finishes

Color tiles intended for reference only.

Color	Code	Description
	0	White
	96	Biscuit
	47	Almond
	NY	Dune
	95	Ice™ Grey
	G9	Sandbar
45	7	Black Black™





Cimarron® Toilet Tank K-5692

No image available. This product is a component and not intended to be a standalone installation.

Technical Information

All product dimensions are nominal. Toilet type: Two-piece

Notes

Install this product according to the installation instructions.

