



# Sunward®

## 66" x 42" drop-in Heated BubbleMassage™ air bath

### K-6347-GH

#### Features

- 120 airjets release thousands of heated bubbles that surround and support the body in a warm massage
- Variable-speed blower lets you adjust massage intensity to 18 levels
- Built-in heater
- Automatic and manual purge cycles remove residual water from air channels after use
- 60-minute automatic shutoff timer
- Oval basin creates a spacious bathing experience
- Spacious design accommodates up to two bathers
- Integral lumbar support and armrests offer extra comfort while bathing
- Keypad control
- Textured bottom surface

#### Material

- Acrylic

#### Technology

- Heated BubbleMassage™ technology warms and humidifies air before it enters the bath

#### Installation

- Drop-in or undermount
- Reversible drain

#### Required Products/Accessories

K-11677 Bath Drain

#### Recommended Products/Accessories

K-738 Under-Mount Install Kit - K-6346/K-6347



#### Codes/Standards

ASME A112.19.7/CSA B45.10  
CSA B45.5/IAPMO Z124  
ASTM E162  
ASTM E662  
UL 1795  
CSA C22.2 No. 218.2  
cUL Listed  
UL Listed

#### KOHLER® Plastic Baths and Shower Bases Lifetime Limited Warranty KOHLER® Hydrotherapy Components Five-Year Limited Warranty

See website for detailed warranty information.

#### Available Colors/Finishes


*Color tiles intended for reference only.*

| Color | Code | Description |
|-------|------|-------------|
|-------|------|-------------|

|                                                                                     |    |         |
|-------------------------------------------------------------------------------------|----|---------|
|  | 0  | White   |
|  | 96 | Biscuit |



**Sunward®**  
66" x 42" drop-in Heated BubbleMassage™ air bath  
**K-6347-GH**



### Required Electrical Service

Two dedicated circuits required, protected with Class A Ground-Fault Circuit-Interrupter (GFCI). Outside North America, this device may be known as a Residual Current Device (RCD).

Blower: 120 V, 15 A, 60 Hz  
Air bath: 120 V, 15 A, 60 Hz

### Technical Information

All product dimensions are nominal.

Drain location: Reversible  
Basin area, bottom: 48-5/8" x 24-1/2" (1235 mm x 622 mm)  
Basin area, top: 60" x 32-3/16" (1523 mm x 818 mm)  
Weight: 122 lbs (55.3 kg)  
Minimum floor load: 34 lbs/ft² (166 kg/m²)  
Water depth: 14-5/16" (364 mm)  
Water capacity: 70 gal (265 L)  
Template: Drop-in, 1233384-7, not required, included  
Electrical component rating: Blower: 120 V, 10 A, 60 Hz  
Air bath: 120 V, 5 A, 60 Hz

### Notes

Measure your actual product for rough-in details.

Install this product according to the installation instructions.

The hot water supply should be 70% of the capacity of the bath or greater. Installations will vary.