

### Technology

- Frameless, 1/4-inch-thick tempered glass with Falling Lines pattern.
- Continuous door panel guide mechanism for smooth, quiet sliding action.
- Gently curved inside and outside towel bars.
- CleanCoat® nanotechnology helps prevent bacteria, mildew and water stains on your glass, making it easy to clean and looking new.
- Out-of-plumb adjustability for easy installation.

### Installation

- Not for use in hospitality.

### Included Components

Additional Components:  
Hardware kit



### Codes/Standards

CPSC 16CFR 1201  
ANSI Z97.1

### KOHLER® One-Year Limited Warranty

See website for detailed warranty information.

### Available Colors/Finishes

*Color tiles intended for reference only.*

Color	Code	Description
-------	------	-------------

	SHP	
--	-----	--


	MX	
--	----	--

	ABV	
--	-----	--

### Available Glass Options

Code	Description
------	-------------

G54	Falling Lines
-----	---------------



### Technical Information

All product dimensions are nominal.

Installation type:	For bath installation
Opening style:	Sliding/Bypass
Opening Width - Min:	56-5/8" (1438 mm)
Opening Width - Max:	59-5/8" (1514 mm)
Walk-through - Min:	24-11/16" (627 mm)
Walk-through - Max:	27-11/16" (703 mm)
Glass thickness:	1/4" (6 mm)
Glass coating:	CleanCoat®

### Notes

Install this product according to the installation guide.

The vertical opening should be a minimum of 57-1/2" (1461 mm) to allow for installation clearance.