

Composed®

moving panel shower door K-706081-ML

Features

 Combines with K-706081-FL fixed panel to create complete K-706081-L shower door.

Material

- Frameless, heavy 3/8" (10 mm) thick Crystal Clear tempered glass movable panel.
- Anodized aluminum hardware prevents rusting or corrosion.

Technology

 CleanCoat® nanotechnology helps prevent bacteria, mildew and water stains on your glass, making it easy to clean and looking new.

Installation

- 78" (1981 mm) high.
- For residential use only.
- Not for use in hospitality.

Included Components

Product consists of:

K-706081-FL fixed panel shower door K-706081-ML moving panel shower door



Codes/Standards

ANSI Z97.1 CPSC 16CFR 1201

KOHLER® One-Year Limited Warranty

See website for detailed warranty information.

Available Colors/Finishes

Color tiles intended for reference only.

Color Code Description

SHP

Available Glass Options Code Description

L Crystal Clear





Composed®

moving panel shower door K-706081-ML



Technical Information

All product dimensions are nominal.

Installation type: For shower base installation

Opening Width - Min: 56-1/8" (1426 mm)
Opening Width - Max: 59-7/8" (1521 mm)
Walk-through - Min: 20-13/16" (529 mm)

Walk-through - Max: 24" (610 mm) Shower Base Radius 3/8" (10 mm)

- Max:

Glass thickness: 3/8" (10 mm)
Glass coating: CleanCoat®

Notes

The vertical opening should be a minimum of 80" (2032 mm) to allow for installation clearance.

