

## Features

- Low-threshold design for easy entry and exit
- Molded-in textured floor
- Water containment bead incorporated into threshold design provides an optimum barrier, preventing water from escaping from shower space
- Single threshold for alcove installation
- Coordinates with Choreograph® shower walls and other KOHLER® collections

## Material

- Acrylic

## Installation

- Right drain

## Recommended Products/Accessories

K-9132 Shower Drain  
K-23726 Drain treatment



## Codes/Standards





CSA B45.5/IAPMO Z124  
ASTM E162  
ASTM E662


## KOHLER® Plastic Baths and Shower Bases Lifetime Limited Warranty

See website for detailed warranty information.

## Available Colors/Finishes

*Color tiles intended for reference only.*

| Color   | Code | Description |
|---|------|-------------|
|  | 0    | White       |
|  | 96   | Biscuit     |
|  | NY   | Dune        |
|  | 95   | Ice™ Grey   |



## Technical Information

All product dimensions are nominal.

|                        |                  |
|------------------------|------------------|
| Drain location:        | Right            |
| Weight:                | 62 lbs (28.1 kg) |
| Minimum flat for door: | 2-5/8" (67 mm)   |

## Notes

Measure your actual product for rough-in details.

Install this product according to the installation instructions.

Subfloor must be within 1/2" (13 mm) of level.

This receptor has a front lip. This should be taken into account when installing a shower door.