

### Features

- Combines with K-SD706080-FL fixed panel to create complete K-SD706080-L shower door
- CleanCoat®+ glass coating creates a hydrophobic barrier that repels water, soap scum, and residue, saving time and protecting shower doors 10 times longer than original CleanCoat. (Based on 2021 internal wear/abrasion testing using a microfiber cloth.)

### Material

- Frameless, heavy 3/8" (10 mm) thick Crystal Clear tempered glass moving panel
- Anodized aluminum prevents rust and corrosion

### Installation

- 78" (1981 mm) high
- For residential use only
- Not for use in hospitality



### Codes/Standards

ANSI Z97.1  
CPSC 16CFR 1201

### KOHLER® One-Year Limited Warranty

See website for detailed warranty information.

### Available Glass Options

| Code | Description   |
|------|---------------|
| L    | Crystal Clear |



**Composed®**  
Moving panel shower door  
**K-SD706080-ML**

**Technical Information**

All product dimensions are nominal.

|                               |                              |
|-------------------------------|------------------------------|
| Installation type:            | For shower base installation |
| Opening Width -<br>Min:       | 44-5/8" (1134 mm)            |
| Opening Width -<br>Max:       | 47-7/8" (1216 mm)            |
| Walk-through - Min:           | 17" (432 mm)                 |
| Walk-through - Max:           | 19-11/16" (500 mm)           |
| Base-To-Wall<br>Radius – Max: | 3/8" (10 mm)                 |
| Glass thickness:              | 3/8" (10 mm)                 |
| Glass coating:                | CleanCoat®                   |

**Notes**

The vertical opening should be a minimum of 80" (2032 mm) to allow for installation clearance.