

Features

- Easy-to-use LCD display and raised, one-touch buttons.
- Integrated diverter lets you toggle between three water outlets.
- Digital thermostatic valve ensures safe and accurate temperature control.
- Warm-up mode reaches set temperature and then pauses until you're ready.
- Additional pause function stops water flow for up to two minutes.
- Countdown mode allows you to set shower duration to save and manage time and water use.
- Ideal for new installation or retrofit to existing shower.

Installation

- Includes prewired plug-and-play electrical connections.
- Install valve up to 20 feet away from the interface with cable supplied.
- Distance can be extended with a standard RJ-11 phone extension cord.

Required Products/Accessories

K-557-K Digital Three-Port Thermostatic Valve
K-559 Interface Mounting Bracket

Loose component/s: 20 ft Cable and adapter included.



Codes/Standards





UL 1951


KOHLER® Faucet Lifetime Limited Warranty

See website for detailed warranty information.

Available Colors/Finishes

Color tiles intended for reference only.

Color	Code	Description
	1CP	Satin Chrome with Polished Chrome
	1SN	Satin Nickel with Polished Nickel
	0	White
	7	Black Black™



Technical Information

All product dimensions are nominal.

Max. Ambient temp: 125°F (51.7°C)

Max. Relative humidity
non-condensing: 100%

Notes

Install this product according to the installation guide.