

# STANDARD CHECK VALVES

# Liberty Pumps®

A Family and Employee Owned Company

## Economy Check Valves



**CV2N1** 1-1/4" and 1-1/2"  
combo

**CV150** 1-1/2"

**CV200** 2"

- ABS valve body
- Rubber slip connect with hose clamps
- Vertical or horizontal installation
- 15 PSI rated at 104°F for CV2N1 and CV150
- 25 PSI rated at 140°F for CV200

## Thread X Barb Fit



**CV150-125T** 1-1/2" MPT  
x 1-1/4" Barb

**CV150-150T** 1-1/2" MPT  
x 1-1/2" Barb

- PVC construction
- Thread directly into 1-1/2" sump pump discharge
- 30 PSI rated at 104°F

## Cast Iron High-temperature 200°F



**HCV150** 1-1/2"

**HCV200** 2"

- Heavy-duty cast iron body
- Full flow
- High-temperature rubber flapper - 200°F
- 125 PSI rated
- Vertical or horizontal installation
- Female NPT connections

## Ball/Check/Union Combination



**BCV150** 1-1/2"

**BCV200** 2"

- Ball/check combo provides compact design
- Heavy-duty PVC
- 150 PSI rated at 72°F
- 30 PSI rated at 140°F
- Vertical or horizontal installation
- Features union for easy disassembly
- Socket weld connections

## Heavy-Duty Compression Fit



**CV2N1C** 1-1/4" and  
1-1/2" combo

**CV200C** 2"

**CV300C** 3"

- Heavy-duty PVC
- Vertical or horizontal installation
- 150 PSI rated at 72°F for CV2N1C and CV200C
- 30 PSI rated at 140°F for CV2N1C and CV200C
- 125 PSI rated at 72°F for CV300C
- 25 PSI rated at 140°F for CV300C

