







BLD107

COCO HAMMERED BUILDER'S SERIES

DETAILS

Hand Crafted Hammered Stainless Steel Installation Type: Drop-In or Undermount Uses 1.5" Drain No Overflow

AVAILABLE FINISHES

PB	Unlacquered Brass - Polished
	Childedagled Blace I chefield

- PS Polished Stainless Steel
- SS Satin Stainless Steel
- UB Unlacquered Brass Satin

AVAILABLE DRAINS

D004	Grid Strainer
	Lift and Turn
D006	Pop-up w/ horizontal lift rod
D101 – D720	Decorative Drain

INSTALLATION

Drain should be installed first.

DROP-IN: Cut opening large enough for the sink to be "dropped in" to countertop.

UNDERMOUNT: Cuts in countertop are up to the discretion of the installer. Clips or other installation method must be provided by the fabricator/installer.

Use 100% silicone to adhere sink to countertop. Clean any excess silicone from sink surface.

CARE

Clean with mild soap. No abrasive chemicals

WARRANTY

Linkasink warranties our product to be free from manufacturing defect for the life of the product. Warranty does not cover abuse.

DIMENSIONS WILL VARY

DO NOT use this sheet as a guide for countertop cuts. Due to the handmade nature of each product, templates are not provided.

Contact: 1.866.395.8377 sales@linkasink.com Linkasink may make changes to specifications without notice. Visit <u>linkasink.com</u> for updated specification sheet. 5/1/2019