

BEFORE YOU BEGIN

We recommend consulting a professional if you are unfamiliar with installing plumbing fixtures. The supplier accepts no liability for any damage to the faucet, plumbing or for personal injury during installation.

Observe all local plumbing and building codes. Unpack and inspect the product for shipping damage. If any damage is found, contact our customer service.

GETTING STARTED

Ensure that you have gathered all the required materials that are needed for the installation.

ADDITIONAL QUESTIONS?

Still need help? Check out our Help Center for product and warranty information, or contact our customer service.

TOOLS AND MATERIALS:



Basin Wrench



Hex Wrench



Adjustable Wrench

INSTALLATION

1. Disassemble the spout, handle, diverter, and hand shower holder bodies and reassemble to attach to the mounting surface.

Note: Remove any set screws with the provided Allen wrench. When all pieces are in the proper position, tighten the set screws to secure.

2. Attach the flexible hoses to the corresponding locations as show in the diagram on the next page. There are 3 flexible hoses and 1 shower hose. Flexible tubes are necessary to ensure there are no kinks or knots.

3. Attach the shower hose to the water feed tube and hand shower.

4. Connect the main water supply lines to the hot and cold handles.

5. After all connections have been made, turn on the water supply, check to make sure that all connections are tight (no water should be leaking) and that the hot and cold supplies are working correctly. Turn the faucet on and allow the water to approximately 60 seconds. Divert the water to the hand shower and allow the water to fl an additional 60 seconds.



Connect hoses as shown:

