

Lead Free CPVC Brass Adapters • Spec Sheet



FEATURES & BENEFITS

- Lead Free CPVC Brass Adapter Fittings
- For use in new and retrofit installations in residential and light commercial plumbing systems.
- Durable over molded one-piece fitting eliminates union tail-piece connection and possible leak path,
- Molded CPVC end piece with slip connection.
- Pressure rated to 100 psi at 180° F / 150 psi at 100° F
- Manufactured to the material and dimensional requirements of ASTM D-2846
- Male and Female threads to ASME B 1.20.1
- Stocked in Sizes 1/2" - 2"

MATERIAL SPECIFICATIONS

No.	Part	Material
1	Nipple	ASTM D1784
2	O-Ring	Rubber (NBR) SN919F
3	Body	Brass C89550

DIMENSIONS

Part #	Size	D	H
CPVCFA03LF	1/2" FIP X 1/2" CPVC	1.12	1.64
CPVCFA04LF	3/4" FIP X 3/4" CPVC	1.39	1.85
CPVCFA05LF	1" FIP X 1" CPVC	1.64	2.25
CPVCFA06LF	1-1/4" FIP X 1-1/4" CPVC	2.09	2.60
CPVCFA07LF	1-1/2" FIP X 1-1/2" CPVC	2.36	2.84
CPVCFA08LF	2" FIP X 2" CPVC FIP	2.92	3.35
CPVCMA03LF	1/2" MIP X 1/2" CPVC	1.12	1.81
CPVCMA04LF	3/4" MIP X 3/4" CPVC	1.39	2.09
CPVCMA05LF	1" MIP X 1" CPVC	1.64	2.60
CPVCMA06LF	1-1/4" MIP X 1-1/4" CPVC	2.09	3.07
CPVCMA07LF	1-1/2" MIP X 1-1/2" CPVC	2.36	3.31
CPVCMA08LF	2" MIP X 2" CPVC	2.92	3.90

• This product complies with 0.25% weighted average lead content on wetted surfaces in accordance with the Safe Water Drinking Act (SDWA) / Federal Public Law No. 111-380.

CPVCFA

CPVCMA

