

SSIM Ice Maker Connectors

Specification Sheet

FEATURES & BENEFITS

- Braided Stainless Steel Connector
- 1/4" Comp x 1/4" Comp
- For use in potable water distribution systems
- Durable, flexible water connector requires no cutting or soldering during installation
- Reinforced PVC inner hose is braided with stainless steel
- Brass hex nuts are plated for corrosion resistance
- 8-sided pneumatic crimp ensures reliable nut-to-hose connection
- Internal corrosion resistance to harsh water conditions



MATERIAL SPECIFICATIONS

| Part No. | Description | Working Temperature | Working Pressure | Approvals |
|-----------|--|---------------------|------------------|----------------------------------|
| SSIM-60LF | 1/4" Comp x 1/4" Comp x 60" Stainless Steel Braided Connectors | 0-158°F | Max. 125 psi | cUPC NSF/ANSI 61 Lead Free |
| SSIM-72LF | 1/4" Comp x 1/4" Comp x 72" Stainless Steel Braided Connectors | 0-158°F | Max. 125 psi | cUPC NSF/ANSI 61 Lead Free |
| SSIM-96LF | 1/4" Comp x 1/4" Comp x 96" Stainless Steel Braided Connectors | 0-158°F | Max. 125 psi | cUPC NSF/ANSI 61 Lead Free |

