

## H 6670 BM

## 30 Inch Speed Oven with combi-modes and Roast probe for precise-temperature cooking.



- TFT clear text display with touch operation - SensorTronic
- Easy cleaning cavity with linenweave pattern & PerfectClean
- The simple way to perfect results automatic programs
- Fresh popcorn at your fingertips thanks to the Popcorn button
- Precise temperature control roasting - Food probe

EAN: 4002515759530 / material number: 10486330	
Construction type	
Built-in wall speed oven	•
Design	
PureLine	•
Appliance color	Clean Touch Steel
Control panel	SensorTronic
Convenience features	
Precise temperature control	75 – 475 °F
Power levels	80/150/300/450/600/850/1
Electronically controlled microwave power	•
Roast probe	•
Operating modes	
Defrost	•
MasterChef automatic programs	More than 100
Auto roast	•
Gentle bake	•
Broil	•
Convection Bake	•
Intensive bake	•
Slow roast	•
Microwave	<del>_</del>
Combi Auto Roast	<del>_</del>
Micro Broil	•
Combi Bake	
Combi Broil	•
Surround	•
Bake	•
Convection Broil	
Special modes	•
Control panel	
MultiLingua	<u>•</u>
Search function automatic programs	•
Popcorn function	
Time of day display	<b>•</b>
Date display	<u>•</u>
Minute minder	<u>•</u>
Time buffer in h	200
Start-stop programming	<u>•</u>
Automatic switch-off	•
Programmable cooking time	•
Entry via number keypad	•
Actual temperature display	•
Default temperatures	•
Acoustic signal when desired temperature is reached	•
Recommended microwave output for each operating mode	•
Minute Plus button	•
Sabbath program	•
Individual settings	•

More information at www.MieleUSA.com



## H 6670 BM

30 Inch Speed Oven with combi-modes and Roast probe for precise-temperature cooking.



Door	
CleanGlass door	•
Door contact switch	•
Door hinge side	Bottom
Cavity	
Cavity volume in cu.ft(l)	1.52 (43)
No. of rack levels	3
No. of halogen lamps	1
Cleaning convenience	
Stainless steel front with Clean Touch Steel surface	•
Stainless-steel cavity with linen surface structure	•
Foldable broil heater element	•
Efficiency and sustainability	
Energy-saving lighting circuit	•
Residual heat utilization	•
Rapid PreHeat	•
Safety	
Appliance cooling system with cool touch front	•
Safety cut-out	<u>•</u>
System lock	•
Door contact switch	•
Technical data	
Niche depth in in. (mm)	21 3/4 (550)
Appliance width in in.(mm)	22 1/16 (559)
Appliance height in in.(mm)	17 5/8 (446)
Weight in lbs. (kg)	94.80 (43.0)
Total connected load in kW	4.0
Fuse rating in A	30
Number of phases	1
Standard accessories	
PerfectClean baking and roasting rack	1
Glass tray	2
Connection wire with plug	•