

TWF160 WP Eco&WiFiConn@ct

T1 Heat-pump tumble dryer
with WiFiConn@ct and FragranceDos.



- Ventless, up to 60% energy savings with heat-pump technology
- Precision drying of all textiles – Perfect Dry
- ENERGY STAR® qualified
- Fragrant laundry just the way you like it – FragranceDos
- Intuitive touch display with 12 programs including Express

EAN: 4002515837290 / material number: 10666280

| | |
|--------------------------------------|----------------------------|
| Construction type | |
| Stackable | • |
| Side-by-Side | • |
| Slot-in | • |
| Door hinging | right |
| Construction type | |
| Heat-pump dryer | • |
| Design | |
| Appliance color | Lotus white |
| Control panel color | Lotus white |
| Door design | Lotus white |
| Rotary selector color | Lotus White / Chrome ring |
| Fascia panel version | 5° incline |
| Control type | Rotary selector |
| Control panel | DirectSensor white, 1 line |
| Drying results | |
| PerfectDry | • |
| FragranceDos | • |
| Intelligent drum reversal | • |
| Gentle laundry care | |
| Honeycomb drum | • |
| Load in lbs. (kg) | 18 (8.0) |
| Control panel | |
| Delay start up to 24 h | • |
| Countdown indicator | • |
| Program sequence indicator | • |
| Drum lighting | LED |
| MultiLingua | • |
| Condensed water container | • |
| Integrated condensed water drainage | • |
| Efficiency and sustainability | |
| EcoFeedback function | • |
| EcoDry technology | • |
| Maintenance-free heat exchanger | • |
| ProfiEco motor | • |

TWF160 WP Eco&WiFiConn@ct

T1 Heat-pump tumble dryer
with WiFiConn@ct and FragranceDos.



| | |
|-------------------------------------|----------------|
| Drying programs | |
| Delicates | • |
| Express | • |
| Outdoor | • |
| Proofing | • |
| Normal | • |
| Wrinkle-free | • |
| Smoothing | • |
| Woolens/Silks | • |
| Dress Shirts | • |
| Time Dry | • |
| Denims | • |
| Table Linens/Drapes | • |
| Bed Linen | • |
| Cold Air | • |
| Basket | • |
| Sportswear | • |
| Settings | • |
| Drying options | |
| Anti-crease action | • |
| Gentle tumble | • |
| Freshen up | • |
| Acoustic signal | • |
| Appliance networking | |
| WiFiConn@ct | • |
| Quality | |
| Soft ribs | • |
| Safety | |
| Lock code | • |
| Empty out container" indicator | • |
| Clean filter" indication | • |
| Optical interface | • |
| Technical data | |
| Dimensions (width) in in.(mm) | 23 1/2 (596) |
| Dimensions (height) in in.(mm) | 33 1/2 (850) |
| Dimensions (depth) in in.(mm) | 25 3/8 (643) |
| Depth with door open in in.(mm) | 42 1/2 (1,077) |
| Weight in lbs. (kg) | 131 (59) |
| Total connected load in kW | 1.0 |
| Fuse rating in A | 15 |
| Length of supply lead in feet (ft.) | 6 (2) |
| Type of coolant | R134a |
| Standard accessories | |
| Fragrance flacon | • |