

H 6780-2 BP2

30 Inch Convection Oven

- The multi-talented Miele for the highest demands.



EAN: 4002516000303 / material number: 10751980

- Multicolored TFT touch display with clear text - M Touch
- Perfect baking and roasting results - Moisture plus
- Precise cooking temperature – Wireless Precision Probe
- Perfect results with ease - - MasterChef Programs
- Unsurpassed room and versatility

<b>Construction type</b>	
Built-in wall oven	•
<b>Design</b>	
ContourLine	•
Appliance color	Clean Touch Steel
Control panel	M Touch
<b>Convenience features</b>	
Precise temperature control	75 – 575 °F
Wireless roast probe	•
Crisp function	•
<b>Operating modes</b>	
Defrost	•
MasterChef automatic programs	More than 100
Auto roast	•
Gentle bake	•
Broil	•
Broil	•
Convection Bake	•
Intensive bake	•
Moisture plus	•
Slow roast	•
Surround	•
Browning	•
Bake	•
Convection Broil	•
Special modes	•
<b>Control panel</b>	
MultiLingua	•
Search function automatic programs	•
Timed bursts of steam	•
Polyphonic acoustic signals	•
Time of day display	•
Polyphonic acoustic signals	•
Date display	•
Minute minder	•
Time buffer in h	200
Start-stop programming	•
Automatic switch-off	•
Programmable cooking time	•
Entry via number keypad	•
Actual temperature display	•
Default temperatures	•
Acoustic signal when desired temperature is reached	•
Sabbath program	•
Individual settings	•
<b>Door</b>	
CleanGlass door	•
Door contact switch	•
Door hinge side	Bottom

More information at [www.MieleUSA.com](http://www.MieleUSA.com)

For further information please see next page...

H 6780-2 BP2

30 Inch Convection Oven

- The multi-talented Miele for the highest demands.



<b>Cavity</b>	
Cavity volume in cu.ft(l)	4.59 (130)
No. of rack levels	6
Labeling of rack levels	•
No. of halogen lamps	3x
TwinPower hot air fans	•
<b>Cleaning convenience</b>	
Stainless steel front with Clean Touch Steel surface	•
Self-cleaning	•
AirClean catalyzer	•
Foldable broil heater element	•
<b>Efficiency and sustainability</b>	
Energy-saving lighting circuit	•
Residual heat utilization	•
Rapid PreHeat	•
<b>Safety</b>	
Appliance cooling system with cool touch front	•
Safety cut-out	•
System lock	•
Door contact switch	•
Door lock during self cleaning	•
<b>Technical data</b>	
Niche depth in in. (mm)	24 1/8 (610)
Appliance width in in.(mm)	28 3/8 (720)
Appliance height in in.(mm)	50 7/8 (1,290)
Weight in lbs. (kg)	341.28 (154.8)
Total connected load in kW	11.0
Voltage in V	240/208
Fuse rating in A	50
Number of phases	1
<b>Standard accessories</b>	
Universal baking tray with PerfectClean	1
Self Clean ready baking and roasting rack	6
Connection wire	•
Connection wire with plug	•