

DA 2698

Insert ventilation hood  
with energy-efficient LED lighting and backlit controls for easy use.



- Customized kitchen design - fully integrated in 34 3/4 (880)Inch width
- Unique user convenience – Con@ctivity
- Energy-efficient and quiet
- Elegant and efficient - edge vented panel

EAN: 4002516023906 / material number: 10876810

<b>Construction type</b>	
Insert ventilation hood	•
<b>Design</b>	
Color	Stainless steel
Edge extraction	•
<b>Operating modes</b>	
Recirculated mode	Convertible
OdorFree charcoal filter (order separately)	DKF19-900
<b>Control panel</b>	
Electronic controls	•
Light-touch controls	•
Power levels (number excl. Intensive)	3
Intensive setting	•
Programmable 'Intensive' switch-off	•
Delayed shutdown for 5 or 15 minutes	•
Programmable grease filter saturation indicator	•
Programmable charcoal filter saturation indicator	•
<b>Cleaning convenience</b>	
Easy-to-clean CleanCover hood liner	•
<b>Efficiency and sustainability</b>	
Power management system	•
Eco package	•
<b>Networking of domestic appliances</b>	
Miele@home	•
WiFiConn@ct	•
Automatic function Con@ctivity 2.0 (Zigbee)	•
<b>Filter system</b>	
Number of dishwasher-safe stainless steel grease filters	2
<b>Lighting</b>	
LED ClearView lighting	•
Light intensity in Lx	650
Color temperature in K	3,500
Light dimmer function	•
<b>Blower</b>	
Dual-action blower	•
DC motor	•
<b>Air throughput with max. duct diameter in vented mode (not for external version)</b>	
Air throughput	Values upon request
<b>Safety</b>	
Safety shut-off	•

DA 2698

Insert ventilation hood  
with energy-efficient LED lighting and backlit controls for easy use.



<b>Technical data</b>	
Canopy width in in.(mm)	34 3/4 (880)
Height of hood canopy in in.(mm)	2 5/8 (64)
Depth of hood canopy in in.(mm)	11 5/8 (293)
Minimum distance above electric cooktops in in.(mm)	24 1/8 (610)
Minimum height above gas cooktop (max. 12.6 kW total power, burner 4.5 kW) in mm	26 (660)
Net weight in lbs. (kg)	31 (14.0)
Length of electrical wire in ft (m)	4 (1.5)
Standard plug fitted	•
Total connected load in kW	0.36
Voltage in V	120
Fuse rating in A	15
Number of phases	1
<b>Installation notes</b>	
Vent connection at top	•
Vent connection at top and rear	•
Diameter of vent connection in in.(mm)	6 (150)
<b>Standard accessories</b>	
Non-return flap	•
Wireless stick Con@ctivity 2.0 for KM	XKS 3000 Z

