

## DA 6798 W Shape

### Wall ventilation hood

with energy-efficient LED lighting and touch controls for simple operation.



- Headroom – design based on Miele built-in appliances
- Unique user convenience – Con@ctivity
- Energy-efficient and quiet
- Safe and easy to clean - Miele CleanCover

EAN: 4002516024613 / material number: 10876860

<b>Construction type</b>	
Wall ventilation hood	•
<b>Design</b>	
Color	Obsidian black
<b>Operating modes</b>	
Recirculated mode	Convertible
OdorFree charcoal filter (order separately)	DKF25-900
<b>Control panel</b>	
Electronic controls	•
Touch controls on glass	•
Power levels (number excl. Intensive)	3
Intensive setting	•
Programmable 'Intensive' switch-off	•
Delayed shutdown for 5 or 15 minutes	•
Programmable grease filter saturation indicator	•
Programmable charcoal filter saturation indicator	•
<b>Cleaning convenience</b>	
Easy-to-clean CleanCover hood liner	•
<b>Networking of domestic appliances</b>	
Miele@home	•
WiFiConn@ct	•
ShopConn@ct	•
Automatic function Con@ctivity 2.0 (Zigbee)	•
<b>Filter system</b>	
Number of dishwasher-safe stainless steel grease filters	1
<b>Lighting</b>	
LED ClearView lighting	•
Light intensity in Lx	320
Color temperature in K	3,500
Light dimmer function	•
<b>Blower</b>	
Dual-action blower	•
AC motor	•
<b>Air throughput with max. duct diameter in vented mode (not for external version)</b>	
Air throughput	Values upon request
<b>Safety</b>	
Safety shut-off	•
Single-ply safety glass (ESG)	•

DA 6798 W Shape

Wall ventilation hood

with energy-efficient LED lighting and touch controls for simple operation.



<b>Technical data</b>	
Overall hood height for vented and external in in.(mm)	22 3/8 (568)
Overall hood height for recirculation in in.(mm)	22 3/8 (568)
Canopy width in in.(mm)	35 3/8 (898)
Height of hood canopy in in.(mm)	22 3/8 (568)
Depth of hood canopy in in.(mm)	19 1/2 (493)
Minimum distance above electric cooktops in in.(mm)	24 1/8 (610)
Minimum height above gas cooktop (max. 12.6 kW total power, burner 4.5 kW) in mm	26 (660)
Net weight in lbs. (kg)	67 (30.0)
Length of electrical wire in ft (m)	2 (0.7)
Standard plug fitted	•
Hard-wired	•
Total connected load in kW	0.36
Voltage in V	120
Fuse rating in A	15
Number of phases	1
<b>Installation notes</b>	
Vent connection at top	•
Vent connection at top and rear	•
Diameter of vent connection in in.(mm)	6 (150)
<b>Standard accessories</b>	
Non-return flap	•
Reducer from 150 to 125 mm Ø	•
Wireless stick Con@ctivity 2.0 for KM	XKS 3000 Z