

DA 4248 V D Puristic Varia

Island décor hood

with energy-efficient LED lighting and backlit controls for easy use.



- Timeless design - 47 1/4 (1,198)Inch wide stainless steel ventilation hood
- Unique user convenience – Con@ctivity
- Motorized chimney
- Pleasantly quiet – Miele Silence package

EAN: 4002515990162 / material number: 10877250

Construction type	
Island ventilation hood	•
Design	
Color	Stainless steel
Customization possible on request	•
Operating modes	
Recirculated mode	air extraction
Control panel	
Electronic controls	•
Light-touch controls	•
Power levels (number excl. Intensive)	3
Intensive setting	•
Programmable 'Intensive' switch-off	•
Delayed shutdown for 5 or 15 minutes	•
Programmable grease filter saturation indicator	•
Acoustic package	•
Hood in Motion	•
Cleaning convenience	
Easy-to-clean CleanCover hood liner	•
Networking of domestic appliances	
Miele@home	•
WiFiConn@ct	•
Automatic function Con@ctivity 2.0 (Zigbee)	•
Filter system	
Number of dishwasher-safe stainless steel grease filters	6
Lighting	
LED ClearView lighting	•
Light intensity in Lx	600
Color temperature in K	3,500
Light dimmer function	•
Blower	
Dual-action blower	•
AC motor	•
Air throughput with max. duct diameter in vented mode (not for external version)	
Air throughput	Values upon request
Safety	
Safety shut-off	•

DA 4248 V D Puristic Varia

Island décor hood

with energy-efficient LED lighting and backlit controls for easy use.



Technical data	
Overall hood height for vented and external in in.(mm)	29 3/4 (755)
Canopy width in in.(mm)	47 1/4 (1,198)
Height of hood canopy in in.(mm)	2 7/8 (70)
Depth of hood canopy in in.(mm)	27 1/2 (698)
Minimum distance above electric cooktops in in.(mm)	24 1/8 (610)
Minimum height above gas cooktop (max. 12.6 kW total power, burner 4.5 kW) in mm	26 (660)
Net weight in lbs. (kg)	109 (49.0)
Length of electrical wire in ft (m)	0 (0.0)
Hard-wired	•
Total connected load in kW	0.51
Voltage in V	120
Fuse rating in A	15
Number of phases	1
Installation notes	
Vent connection at top	•
Diameter of vent connection in in.(mm)	6 (150)
Telescopic chimney	•
Standard accessories	
Non-return flap	•
Wireless stick Con@ctivity 2.0 for KM	XKS 3000 Z

