



HIGH VISIBILITY CUT LEVEL 2 POLYURETHANE DIPPED GLOVES

BETTER FIT. BETTER PROTECTION.

EN388



3242B



EN388 STANDARDS						
Abrasion	1	2	3	4	-	-
Cut Resistance (Coup Test)	1	2	3	4	5	X*
Tearing	1	2	3	4	-	-
Puncture	1	2	3	4	-	-
Cut Resistance (TDM Test)	A	B	C	D	E	F

*If the coupe test provides a 3 or above it is marked as an "X" for not applicable and uses the TDM 100 test instead

**SMARTWIPE™ Touch
Screen Compatible
Fingertips**

**Reinforced
Nitrile Coating**

**Polyurethane
Better fit**



**Light and
Breathable Back**

**Color-Coded Bands
Easy cut level
identification**

SPECIFICATIONS	
Gauge	15
Liner Material	Polyester and HPPE Blend Knit
Dip Material	Polyurethane
Cuff Style	Elasticated Knit

RECOMMENDED APPLICATIONS
<ul style="list-style-type: none"> Light Demolition Light Material Handling General Work High-Dexterity Applications Wire Stripping

CARE INSTRUCTIONS
Machine wash warm water (105°F), mild detergent, no bleach. Line dry.

SIZE	1 PAIR	12 PAIR (Contractor Pack)
S	48-73-8920	48-73-8920B
M	48-73-8921	48-73-8921B
L	48-73-8922	48-73-8922B
XL	48-73-8923	48-73-8923B
XXL	48-73-8924	48-73-8924B

**SEE
MORE
PPE**



or visit <https://qr.mke.tl/2qm6s>